

Master Series Electric XPress Grill With Active Compression

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approved _____
 Date _____

Master Series Electric XPress Grill With Active Compression

Models

- XPE12AC



Model XPE12AC
shown with low-profile grease cans



90 degree
NEMA plug

Standard Features

- Programmable control for each cooking lane precisely controls:
 - Automatic lifting and lowering of upper platen
 - Cooking gap and time
- EasyTouch™ screen design is simple and intuitive with Press and Go interface
- Advanced temperature control, smart anticipation versus on-off:
 - Eliminates temperature overshoot and undershoot
 - Increases temperature uniformity with five independently controlled heat zones - three on lower plate and two on upper platen
- Recipes are programmed by setting grill temperature, platen temperature, cook time.
- Option to choose a maximum 1-inch or 2-inch cook gap:
 - 1-inch cook gap:
 - Cook food product up to 1 inch thick
 - Maximum platen opening angle is 50 degrees
 - 2-inch cook gap:
 - Cook food product up to 2 inches thick
 - Maximum platen opening angle is 42 degrees
- Allowable active compression cooking
- USB interface to update menus
- User interface provides advanced diagnostics and error logging for ease of service and increased first-time fix
- Stainless steel front, top and sides
- Towel bar with bun pan lip
- Stainless steel dual side grease collectors
- Splash guard
- Swivel casters (4) with front brakes
- Hatchless cowl for protection from water during cleaning
- IPX4 water resistant rating
- Two year limited parts and labor (USA & Canada)
- Cleaning kit with high temperature grill cleaner and cleaning tools/accessories, provided with every grill.

Optional

- Universal Tool Holder (1 or 2)
- UHC tray holder

Specifications

The XPress Grill's upper and lower grill plates cook both sides simultaneously, reducing cook times by up to 50%.

Upper grill plate is automatically raised and lowered by a lift system powered by a quiet actuator.

Lower griddle plate made of 3/4" (19mm) thick carbon steel, machine ground and highly polished.

Lower grill plate heated by three electric heating elements.

Upper platen heated by nickel-plated cast aluminum electric heating elements.

Electric top heater provided with replaceable quick release Teflon sheets.

Available in three phase power for Delta or Wye

electrical systems.

Voltage sensing detects brownouts and electrical input issues. Power calibration feature adjusts power output based on electrical system voltage.

Available with CSA or CE approvals.

All have NSF approval.

Installation with zero clearance against non-combustible surfaces.



Master Series Electric XPress Grill With Active Compression

PLATEN WIDTH
11.300in
[292mm]

OVERALL DEPTH
34.501in
[876mm]

GRILL PLATE DEPTH
22.000in
[559mm]

PLATEN LENGTH
20.000in
[508mm]

GRILL PLATE WIDTH
12.250in
[311mm]

GRILL PLATE DEPTH
19.750in
[502mm]

OVERALL WIDTH
15.352in
[390mm]

CONDUIT (5.25in)
[133mm]

GRILL PLATE TO GREASE DRAWER SIDE SPLASH
2.671in
[68mm]

GREASE DRAWER DEPTH
7.375in
[187mm]

ELECTRICAL
3.787in
[96mm]

OVERALL HEIGHT
32.289in
[820mm]

11.348in
[288mm]

SHOWN WITH PLATEN REMOVED

5.625in
[143mm]

9.000in
[229mm]

4.250in
[109mm]

7.50in
[191mm]

COOK ZONE DEPTH
19.750in
[502mm]

GREASE DRAWER LENGTH
31.439in
[799mm]

COOK ZONE WIDTH
11.250in
[286mm]

GREASE DRAWER WIDTH
1.746in
[44mm]

WORK HEIGHT MAX.
33.563in
[853mm]

WORK HEIGHT MIN.
29.875in
[759mm]

SHOWN WITH GREASE DRAWERS REMOVED

A

B

C

D

ELECTRICAL
6.999in
[178mm]

CASTER HEIGHT MIN.
5.966in
[152mm]

CASTER HEIGHT MAX.
11.654in
[296mm]

CASTERS (TYP)
Ø 4.000in
[102mm]

Cook Gap	Dimension			
	A	B	C	D
1-inch	1.000 in	50 deg	23.009 in	61.267 in
	25 mm		584 mm	1556 mm
2-inch	2.125 in	42 deg	20.018 in	58.507 in
	54 mm		508 mm	1486 mm

Weight

Product (grill only), 492lbs.
Packaged for shipping (accessories included), 558lbs.

Electrical Input Specification - North America, Central America, and South America					
CSA Approved Models					
Model	Volts 3Ph (Delta) 50/60 Hz	Total Current (A)			Power (kW)
		L1	L2	L3	
XPE12AC 1 Platen	200V	23.1	26.6	24.7	8.0
	208V	21.3	23.9	22.8	7.6
	220V	21.4	24.0	22.6	7.9
	230V	21	23.1	22.0	7.9
	240V	21	22.5	21.8	7.9

Cords - The Americas - DELTA		
Country	Factory Installed	Plug Options
USA	Yes	NEMA 30A. right angle
Canada	Yes	NEMA 30A. right angle
Other	No	Customer Provided

For pin & sleeve plug, order installation kit

Electrical Input Specification - Exports					
CE Approved Models					
Model	Volts 3Ph (WYE) 50/60 Hz	Total Current (A)			Power (kW)
		L1	L2	L3	
XPE12AC 1 Platen	220V/380V	12.6	15.5	13.9	7.9
	230V/400V	11.8	15.3	13.9	8.0
	240V/415V	11.8	15.0	13.9	8.0

Cords - Exports - WYE		
Country	Factory Installed	Plug Options
Various	Yes	IEC 32A Pin & Sleeve

Garland reserves the right to make changes to the design or specifications without prior notice.

Garland Commercial Ranges Ltd.
1177 Kamato Road,
Mississauga, Ontario
L4W 1X4 CANADA

General Inquires 1-905-624-0260
USA Sales, Parts and Service 1-800-424-2411
Canadian Sales 1-888-442-7526
Canada or USA Parts/Service 1-800-427-6668

www.garland-group.com
8030A
01/25

