



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
EERM-2 R-290 UK 230V 50/60Hz 1N

19097099

04/05/2023

The photo may show the standard model and not the configured one

DENOMINATION:

Refrigerated wall displays ERM series (black plastic covered), with 2 doors, at 50Hz.

DESCRIPTION :


Refrigerated wall displays ERM SERIES (black plastic covered).

DESCRIPTION:

- Sanitary epoxy coated galvanised steel inside.
- Black plastic covered galvanised steel (black version).
- 40 kg/m³ injected polyurethane insulation.
- Copper piping and aluminium flaps evaporator.
- Hermetically sealed copper serpentine ventilated compressor.
- Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
- Digital display for electronic control of temperature.
- ON/OFF power switch.
- Top horizontal lightning.
- Working temperature: +2 °C, +8 °C (room temperature: 32 °C).
- UK plug

DIMENSIONS

X Width	925 mm	X Gross width	970 mm
Y Depth	565 mm	Y Gross depth	615 mm
Z Height	900 mm	Z Gross height	1055 mm
Net Weight	80,0 kg	Gross Weight	83,0 kg
Net volume	0,470 m ³	Gross volume	0,629 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,280 kW
Amperage (A)	1,62 A
Voltage	230V - 1N
Electric frequency	50/60Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-290
----------	-------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,369 kW
Annual elec. consumption	1175,30 kWh
Power consumption 24h	3,22 kWh
Climate class	4
Cooling gas load	59,000 g
Clasif. Energy efficiency	G
Energy Efficiency Index	91,54 %

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

OTHERS

Number of doors	2
Condensation system	Vent.







Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
EERM-2 R-290 UK 230V 50/60Hz 1N

19097099

04/05/2023

The photo may show the standard model and not the configured one



	EERM	EERMU
X	900	800

