

CULITEK Undercounter Refrigerators & Freezers

Models: MRUCRF-27, MRUCRF-48, MRUCRF-60, MRUCRF-72 MRUCFZ-27, MRUCFZ-48

EQUIPMENT THAT DOMINATESFor Culinary Professionals





Undercounter Refrigerators and Freezers

Keep foods cold and easily accessible with these compact undercounter refrigerators from CULITEK. Constructed of heavy-duty, stainless steel, these units fit under your countertop making them the perfect solution to adding more space anywhere you need. The flat stainless steel countertop allows for them to be used as a separate workstation. All undercounter units come with 4" casters and plastic coated wire shelving. Models are ETL Listed and ETL Sanitation, and are backed with a 2 year warranty on parts and a 5 year warranty on the compressor.

Cooling System

- R290 hydrocarbon refrigerant is an environmentally-responsible choice for your business.
- · Maintains a temperature range of 33°F to 41°F (refrigerators) and -8°F to 0°F (freezers)
- · Rugged built axial evaporator fans run efficiently with low velocity and high volume air flow

Cabinet Construction

- · Exterior is constructed of 430 corrosionresistant stainless steel, including doors
- · Interior is constructed of 304 corrosionresistant stainless steel
- · Insulated cabinet with foamed-in-place, high density cell polyurethane insulation

Electrical Control

- · LED temperature display provides easy temperature adjustment when necessary
- · Carel temperature controller initiates automatic defrost cycle for worry-free use
- 7-foot power cord with NEMA 5-15 plug

Door(s)

- · Stainless steel exterior
- · Positive self-closing doors with microswitch that shuts the evaporator fans off when the door is open
- · Recessed handles are built into the door for easy opening and closing
- · Removable door gasket for easy cleaning

Shelving

- · Adjustable plastic coated steel shelves have a load capacity of 90 lbs. per shelf
- · Shelving installed with K-clips

Model Features

- 4" casters come standard on all stainless steel models, 2 locking wheels and 2 non-locking wheels
- · Stainless steel top is 2" thick

STANDARD FEATURES

- Easy to clean, 430 series stainless steel exterior
- Interior constructed of 304 stainless steel
- Digital temperature control ranges 33°F to 41°F in refrigerators and -8°F to 0°F in freezers
- **Epoxy coated, corrosion** resistant shelves with 90 lb. capacity per shelf
- Self-closing door, with microswitch that shuts the evaporator fans off when door is open
- Preprogrammed digital control featuring auto-defrost cycle
- Foamed-in-place insulation helps provide strength, while helping to maintain internal temperature
- **Eco-friendly R290 hydrocarbon** refrigerant
- All models come with 4" casters







Attention CA Residents **PROP 65 WARNING**

This product can expose you to chemicals, including lead, which are known to the State of California to cause cancer, birth defects, or other reproductive harm.

For more information, go to www.P65warnings.ca.gov


MADE IN CHINA



MRUCRF-27, MRUCFZ-27

35.25"

27"




























UNDERCOUNTER F	REFRIGERATORS MRUCRF-27	MRUCRF-48	MRUCRF-60	MRUCRF-72
Doors	1	2	2	3
Shelves	1	2	2	3
Net Volume (Cu. Ft.)	6.3	12	17	21
Overall Dimensions (in)	27"W x 29.5"D x 35.25"H	47.25"Wx29.5"Dx35.25"H	60"W x 29.5"D x 35.25"H	71.5"W x 29.5"D x 35.25"H
Interior Dimensions (in)	22"W x 23"D x 23.5"H	42.5"W x 23"D x 23.5"H	55.5"W x 23"D x 23.5"H	67"W x 23"D x 23.5"H
Horsepower	1/6	1/5	1/5	1/5
Refrigerant	R290	R290	R290	R290
Voltage/Hertz/Phase	115/60/1	115/60/1	115/60/1	115/60/1
Amps	1.9	2.7	2.9	3.2
Net Weight (lbs)	169	238	282	364
Gross Weight (lbs)	220	299	326	408
Shipping Dimensions (in)	29.7"W x 32.5"D x 38.5"H	50"W x 32.5"D x 38.5"H	63"W x 32.5"D x 38.5"H	50"W x 32.5"D x 38.5"H

UNDERCOUNTER FREEZERS						
Model Number	MRUCFZ-27	MRUCFZ-48				
Doors	1	2	-	-		
Shelves	1	2	-	-		
Net Volume (Cu. Ft.)	6.3	12	-	-		
Overall Dimensions (in)	27"W x 29.5"D x 35.25"H	47.25"Wx29.5"Dx35.25"H	-	-		
Interior Dimensions (in)	22"W x 23"D x 23.5"H	42.5"W x 23"D x 23.5"H	-	-		
Horsepower	1/5	1/4	-	-		
Refrigerant	R290	R290	-	-		
Voltage/Hertz/Phase	115/60/1	115/60/1	-	-		
Amps	2.1	3.12	-	-		
Net Weight (lbs)	178	251	-	-		
Gross Weight (lbs)	233	312	-	-		
Shipping Dimensions (in)	29.7"W x 32.5"D x 38.5"H	50"W x 32.5"D x 38.5"H	-	-		