

Maintain ideal serving temperatures to keep prepared food warm and appetizing under these infrared, twin-bulb heat lamps, featuring maximum adjustability, improved countertop stability and an easy-to-clean, scratch-resistant finish.

- ◆ Compatible with most standard-size food trays
- ◆ Heavy-duty frame with 13 gauge aluminum bulb hoods
- ◆ Two (2) clear, infrared shatter-resistant 250W/120V bulbs included



3-POSITION ELECTRIC STEEL TUBING HEAT LAMPS

- ◆ Easy-clean, durable, scratch-resistant electrostatic powder-coated finished hoods and frame
- ◆ 3-position adjustable height to control heat intensity

OVERALL DIMENSIONS L" X D" (mm)	ADJUSTABLE HEIGHT" (mm)	POWER	PLUG & CORD	SHIP WEIGHT
19-1/2 x 22-1/2 (495 x 571)	23-5/8 (600mm) 26-1/8 (664mm) 28-5/8 (727mm)	120V~50/60Hz, 500W, 4.2A	NEMA 5-15P 70" (178cm) long cord	6.6 lbs (3 kgs)
BASE DIMENSIONS L" X D" (mm)				
18 x 14 (457 x 356)				

ITEM	DESCRIPTION	UOM	CASE
EHL-3C	3-Position Heat Lamp, Black	Set	1
EHL-2C	3-Position Heat Lamp, Gray	Set	1

Heat lamps include 2 clear,
infrared shatter-resistant
250W/120V bulbs



4-POSITION ELECTRIC ALUMINUM TUBING HEAT LAMP

- ◆ 14 gauge heavy-duty aluminum tubing frame
- ◆ Easy-clean brushed aluminum finish
- ◆ 4-position adjustable height to control heat intensity

OVERALL DIMENSIONS L" X D" (mm)	ADJUSTABLE HEIGHT" (mm)	POWER	PLUG & CORD	SHIP WEIGHT
19-1/2 x 22-1/2 (495 x 571)	29-3/8 (746mm) 27-1/2 (699mm) 25-1/2 (648mm) 23-3/4 (603mm)	120V~50/60Hz, 500W, 4.2A	NEMA 5-15P 70" (178cm) long cord	7.5 lbs (3.45 kgs)
BASE DIMENSIONS L" X D" (mm)				
16-1/4 x 14-1/4 (413 x 362)				

ITEM	DESCRIPTION	UOM	CASE
EHL-2	4-Position Heat Lamp, Aluminum	Set	1

Refer to page 224 for food pans



INFRARED SHATTER-RESISTANT BULBS FOR HEAT LAMPS

- ◆ Shatter-resistant infrared 250W/120V bulbs
- ◆ R40 bulb with medium E26 base
- ◆ Up to 6,000 hours burn time
- ◆ For commercial food-operations only

ITEM	DESCRIPTION	UOM	CASE
EHL-BR	Red	Each	1/12
EHL-BW	Clear	Each	1/12

ELECTRIC HEAT LAMPS



INFRARED R40 BULBS



Retail Box
Design



EHL-BW



EHL-BR

