

# Drop-in Refrigerated Cold Wells

PRODUCT: QUANTITY:

Models: ☐ CW-1 ☐ CW-2 ☐ CW-3 ☐ CW-4 ☐ CW-5 ☐ CW-6

### **Designed Smart**

### **Compact Design with High Output**

The Drop-In Cold Well provides an economic solution to the cost of in-counter refrigeration.

- Uses R-134a refrigerant.
- Can hold cold food at 34°F to 40°F for extended periods.
- Interior temperature is factory set, but can be field adjusted depending on unit's application.

### **APW Wyott Design Features**

- Holds standard steam table pans
- Energy saving
- Field adjustable temperature
- · Stainless steel construction with fully insulated walls
- Supplied with 6 ft. cord and NEMA 5-15P plug
- Drain provided

### **Option and Accessories**

- COMP-5 5-year compressor warranty
- Pan dividers standard



Model: Drop-In Cold Well

# Reliability backed by APW Wyott's Warranty

APW Wyott Drop-In Cold Wells are backed by a 1-year parts and labor warranty, including on-site service calls within 50 miles of authorized service technicians.

### Certified by the following agencies:








See reverse side for product specifications.





# Drop-in Refrigerated Cold Wells

Models: □ CW-1 □ CW-2 □ CW-3 □ CW-4 □ CW-5 □ CW-6
PRODUCT: QUANTITY: ITEM:



#### PRODUCT SPECIFICATIONS

#### Construction:

Interior is stainless steel; exterior is aluminized steel

Freight Class: 70 FOB: Allen, TX 75013

| INSIDE DIMENSIONS |                  |                    |  |  |  |
|-------------------|------------------|--------------------|--|--|--|
| Model             | Width            | Length             |  |  |  |
| CW-1              | 13 1/2" (34.3cm) | 22" (55.9cm)       |  |  |  |
| CW-2              | 22" (55.9cm)     | 26 13/16" (68.1cm) |  |  |  |
| CW-3              | 22" (55.9cm)     | 40 1/8" (101.9cm)  |  |  |  |
| CW-4              | 22" (55.9cm)     | 53 7/16" (135.7cm) |  |  |  |
| CW-5              | 22" (55.9cm)     | 66 3/4: (169.5cm)  |  |  |  |
| CW-6              | 19 7/8"          | 80 1/2"            |  |  |  |

#### **Electrical SPECIFICATIONS**

| MODEL | VOLTS | Hz | PHASE | AMPS | COMPRESSOR | CHARGE         |
|-------|-------|----|-------|------|------------|----------------|
| CW-1  | 120   | 60 | 1     | 4    | 1/5 HP     | 8.75 ozR134A   |
| CW-1  | 230   | 50 | 1     | 2    | 1/5 HP     | 8.75 ozR134A   |
| CW-2  | 120   | 60 | 1     | 5    | 1/4 HP     | 9.50 ozR134A   |
| CW-2  | 230   | 50 | 1     | 2    | 1/4 HP     | 9.50 ozR134A   |
| CW-3  | 120   | 60 | 1     | 5    | 1/4 HP     | 10.0 ozR134A   |
| CW-3  | 230   | 50 | 1     | 2    | 1/4 HP     | 10.0 ozR134A   |
| CW-4  | 120   | 60 | 1     | 5    | 1/4 HP     | 11.0 ozR134A   |
| CW-4  | 230   | 50 | 1     | 2    | 1/4 HP     | 11.0 ozR134A   |
| CW-5  | 120   | 60 | 1     | 5.5  | 1/3 HP     | 12.0 ozR134A   |
| CW-5  | 230   | 50 | 1     | 2.8  | 1/3 HP     | 12.0 ozR134A   |
| CW-6  | 115   | 60 | 1     | 15.3 | 1/3 HP     | 54 oz. – R404A |

#### **DIMENSIONS**

| MODEL | DIMENSIONS                     | RECOMMENDED CUT OUT |
|-------|--------------------------------|---------------------|
| CW-1  | 28"L x 19 1/2"W x 23 13/16"H   | 26 1/2" x 18"       |
| CW-2  | 32 13/16"L x 28"W x 23 13/16"H | 26 1/2" x 31 5/16"  |
| CW-3  | 46 1/8"L x 28"W x 23 13*16"H   | 26 1/2" x 44 5/8"   |
| CW-4  | 59 7/16"L x 28"W x 23 13/16"H  | 26 1/2" x 57 15/16" |
| CW-5  | 72 3/4"L x 28"W x 23 13/16"H   | 26 1/2" x 71 1/4"   |
| CW-6  | 86"L x 25 3/8" x 24.5"H        | 23 7/8" x 841/2"    |

<sup>\*</sup>APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.

