



# SLICER VML-350 230/50/1

Blade Ø 350 mm. Belt-driven.



5051044

## SPECIFICATIONS



Blade diameter: 350 mm  
Cutting capacity: 250 mm x 360 mm  
Slice thickness: 0 mm - 16 mm  
Carriage run: 430 mm  
Total loading: 370 W  
IP Protection grade: IP-X1  
Electrical supply: 230 V / 50 Hz / 1~  
Plug: EU

### External dimensions (W x D x H)

- ✓ Width: 920 mm
- ✓ Depth: 680 mm
- ✓ Height: 670 mm

Net weight: 43 kg

### Crated dimensions

640 x 830 x 700 mm  
Gross weight: 50 kg

## SALES DESCRIPTION

**Vertical position for universal application. Special for fresh meat.**

- ✓ Slicer fully made of high-polished aluminium protected against anodic oxidation.
- ✓ Built-in precision sharpener.
- ✓ Universal cutting blade with relief.
- ✓ Protection ring against water and grease entry to the blade mechanism.
- ✓ Decimal cutting thickness adjustment from 0 mm to 16 mm.
- ✓ Base made of a single piece, mounted on bearings.
- ✓ Equipped with blade protection ring and carriage lock.
- ✓ Luminous double on/off 24V switch.
- ✓ Electronic safety plate.
- ✓ Easy cleaning, no need for tools. Removable and dishwasher-safe grip points.
- ✓ The greater distance between the box and the blade facilitates cleaning.



[www.sammic.co.uk](http://www.sammic.co.uk)

Food Service Equipment Manufacturer

Unit 2, Trevanth Road  
Troon Industrial Park  
LE4 9LS - Leicester

[uksales@sammic.com](mailto:uksales@sammic.com)  
Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

product sheet  
updated 25/01/2024

DYNAMIC PREPARATION  
COMMERCIAL SLICERS