



British Manufacturing
since 1957



The Professionals Choice

CTS19F

SureFlow Counter-Top Water Boiler with built in Filtration



FULL SPECIFICATION



SureFlow Counter-Top Automatic Fill Water Boiler with Built-in Filtration

Type	Countertop - <i>Standard Range</i>
Country of Design & Manufacture	UK
<u>CAPACITY, WEIGHTS & DIMENSIONS:</u>	
Capacity (Litres)	19
Unit dimensions (W x D x H) mm	243 x 510 x 668 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	425 x 595 x 825
Tap clearance mm	190mm
Product weight - empty (kg)	14.8
Product weight – full (kg)	33
Packed weight (kg)	18.2
<u>CONSTRUCTION:</u>	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
<u>ELECTRICAL:</u>	
Power rating (kW)	6
Voltage supply	220-230 V (50-60Hz)
Electrical supply	Single-phase, N & E (32A)
Electrical Connection	Wire to min 32A single-phase supply via an isolation switch
Fitted cable length (m)	1.7m
<u>PLUMBING:</u>	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Front via drip-tray (or rear using kit not supplied)
<u>PERFORMANCE:</u>	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	21.5 mins (full tank capacity)
Output per hour (@ default temperature setting)	57 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	19 Litres
Recovery per minute	1 Litres
Stand-by power loss (idle mode)	0.09 kW/h
<u>FILTRATION:</u>	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	Yes
Filter Benefits	Latest triple-action; removes sediment & impurities such as chlorine and reduces limescale build-up
Mechanical sediment filtration	3 micron
Filter counter programmable	Yes (soft, medium & hard water settings)
<u>OTHER FEATURES:</u>	
Tank-baffle plates – unique design aids heat recovery & reduces steam emissions to atmosphere	Yes
Early warning lime-scale diagnostics (via LCD screen)	Yes – Standard
Dual safety protection	Yes - Over-boil & boil-dry protection
<u>STANDARDS & APPROVALS:</u>	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (EN 60335-1 & 2)
<u>WARRANTY & AFTER-SALES:</u>	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited
T: 01704 501114
F: 01704 501115
E: sales@instanta.com



Certificate Numbers: FM36413 & EMS75807