BEVERAGE-AIR

PROJECT: _____

ITEM # _____ QTY: _____

MODEL # _____

AIA # _____ SIS # _____

APPROVED: _____

# WORKTOP FREEZERS

## Model: WTFD60AHC-4-FLT

### FOUR DRAWER / FLAT TOP

## 7 YEAR WARRANTY

### Parts, Labor, and Compressor



## CABINET CONSTRUCTION

- Stainless steel front, sides, drawers and grille (galvanized back & bottom)
- Interior liner is made of corrosion resistant aluminum
- Stainless steel worktop for added durability
- Full electronic control
- Flat top
- Interior thermometer is standard
- Snap-in drawer gaskets
- Upper and lower pull-out drawers accommodate 6" deep pans
- Stainless steel drawer frames supported on telescoping drawer slides
- Drawer slides include locking mechanism that prevents drawer from being inadvertently pulled off cabinet
- 6" Casters, two (2) with brakes standard

## OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- Cutting board
- Full electronic control
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- Low profile casters
- Roller kit
- Remote option* (see note on back on page)

## REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Freezers capable of maintaining product temperature of -10°F

3779 Champion Blvd., Winston-Salem, NC 27105
888-845-9800 Fax: 336-245-6453
Beverage-Air.com Sales@bevair.com


Please verify qualifying units by visiting:
www.energystar.gov/cfs

Specifications are subject to change without prior notice.
Date Issued 11/26 Printed in U.S.A.


# BEVERAGE-AIR

## Worktop Freezers
## Model: WTFD60AHC-4-FLT


PLAN VIEW




ELEVATION VIEW




SIDE VIEW




| EXTERNAL DIMENSIONAL DATA | |
|---|---|
| Width Overall (in) | 60” |
| Depth Overall (in) | 32” |
| Height Overall (in) | 35 5/8” |
| Number of Drawers | 4 |
| Depth with Drawer Extended | 47 1/2” |
| Drawer Openings | (4) 22 5/8” x 9 3/8” |
| **INTERNAL DIMENSIONAL DATA** | |
| NET Capacity (cubic ft). | 14.36 |
| Internal Width Overall (in) | 56” |
| Internal Depth Overall (in) | 15 3/8” |
| Internal Height Overall (in) | 23” |

### ELECTRICAL CONNECTION

115/601
NEMA 5-15P

Unit pre-wired at factory and include 8’ long cord and plug set.

| ELECTRICAL DATA | |
|---|---|
| Full Load Amps | 5.0 |
| Voltage | 115/60/1 |
| Nema Plug (8’ cord) | 5-15P |
| **REFRIGERATION DATA** | |
| Horsepower | 1/2 |
| Capacity (BTU/Hr) | 1868 |
| Heat Rejection (BTU/Hr) | 2802 |
| Charge (lbs/grams/ounces) | 0.165 / 75 / 2.64 |
| **SHIPPING DATA** | |
| Gross Weight - Crated | 392 lbs. |
| Height - Crated (in) | 38” |
| Width - Crated (in) | 63” |
| Depth - Crated (in) | 33” |

*NOTE: Remote units are field wired and come with 6” legs.
Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4”. Metric dimensions (MM).

Required Clearance: 3” Bottom & 2” Rear


3779 Champion Blvd., Winston-Salem, NC 27105 | 888-845-9800 | Fax: 336-245-6453 | Beverage-Air.com | Sales@bevair.com



Date Issued 11/26 | Printed in U.S.A.



WELBILT
an Ali Group Company