



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
ACP-2G C CI 230V 1N 50Hz

19089933

23/01/2024

**DENOMINATION:**

Refrigerated counter - Advance 700 Gastronorm with 2 doors.

**DESCRIPTION :**

- Structure built with AISI-304 stainless steel
  - 50 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
  - Forced draught cooling system inside the room.
  - Copper piping and aluminium flaps evaporator.
  - Digital display for electronic and digital control of temperature and defrosting.
  - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
  - Easier loading and unloading thanks to its door self-closing and stay open features.
  - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
  - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
  - Built-in drainage to get rid of waste liquids inside the unit.
  - Interior LED lighting (only for models with glass doors).
  - Embedded bottom and curved panels inside for easy cleaning and maintenance.
  - Height adjustable stainless steel legs.
  - 10 cm high splashback.
  - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
  - Tested in climatic class IV.
- Refrigerated counters.

**POSSIBLE OPTIONS :**

- Stainless Backing
- Legs instead of castors
- Door frame resistance
- Glass door
- Granite worktop
- Drawers [1/2] unit
- Locks
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture
- Remote group
- Drawers [1/3] unit
- Drawers [1/3 + 2/3] unit

**STANDARD OPTIONS :**


- HACCP alarm
- Castors
- UK plug

**POSSIBLE ACCESSORIES :**

- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

**DIMENSIONS**

X Width	1340 mm	X Gross width	1455 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	107,0 kg	Gross Weight	112,0 kg
Net volume	0,803 m <sup>3</sup>	Gross volume	1,200 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Amperage (A)	0,8 A
Electric frequency	50Hz
Electric power	0,152 kW
Voltage	230V - 1N

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Annual elec. consumption	381,00 kWh
Clasif. Energy efficiency	A
Climate class	4
Cooling gas load	103,000 g
Energy Efficiency Index	17,17 %
Gross internal volume	258 L
Model Type	Counter Cabinet
Power consumption 24h	1,05 kWh
Refrigeration net.vol	173 L
Refrigeration power	0,361 kW

**OTHERS**

Condensation system	Vent.
Number of doors	2





**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
ACP-2G C CI 230V 1N 50Hz

19089933

23/01/2024

**SUPPLIED ACCESSORIES:**

- 12035781 GN 1/1 grid in epoxy (530x325) 2
- 12036880 Advance table grill guide - wall and central - 519 mm - 1 piece 8



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**REFRIGERATION**

**Specific model**  
ACP-2G C CI 230V 1N 50Hz

19089933

23/01/2024

