

Optimax refrigerated assisted service Patisserie Style Display

FCSI/CESA Sustainable Catering Equipment Award 2012 - Highly Commended.

Counter Units

Model No: RMR65E - 650mm unit

Model No: RMR100E - 1000mm unit

Model No: RMR130E - 1300mm unit

Unit Shown RMR100E with black plastic coated steel base fascia panels. Optional undershelf lighting, ticket strips and castor cover

Product Specification

Dimensions

Model - - - - - Top size - - - - - loading

RMR65E - - - 650 x 750 x 1445mm high - 1.8kW

RMR100E - 1000 x 750 x 1445mm high - 2.5kW

RMR130E - 1300 x 750 x 1445mm high - 2.7kW

Electrical Connection

220V/240V, 1 phase, 50 Hz.

Cable

Units fitted with 2 metres of cable and 13 amp plug.

Refrigerant

R404a CFC free refrigerant

Construction

Bright polished & satin finish stainless steel with toughened glass screens.

Choice of stainless steel, coloured plastic coated steel or wood laminate base fascia panels.

Operating conditions

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005

Performance level M1 (-1°C to + 5°C) in Climate class 3 (25°C, 60%RH,0.2m/s)

Additionally our own testing has shown that Optimax refrigerated units will maintain core product temperature of pre-chilled food below + 5°C in ambient temperatures up to 27°C at 50% relative humidity

The assisted service models feature a full height toughened curved glass screen to the front with a unique drop-down / lift-up rear door arrangement.



Product Features

- Microprocessor based temperature control with automatic defrost and condensate handling system.
- Illuminated display via integral fluorescent lighting.
- Three removable 8mm toughened glass shelves. The top and lower shelves are height adjustable for flexibility of display.
- Option of fluorescent lighting under each shelf.
- Supplied on four low level castors.
- Stainless steel recessed top with removable recessed well for service access and cleaning.
- Enclosed toughened curved glass front screen hinged for ease of cleaning.
- Unique rear door arrangement helping to maintain cabinet temperatures when doors are opened.

Extras

Under shelf lighting

Shelf edge ticket strips

Castor covers - satin finish stainless steel covers