

Stealth® Tray Delivery Carts

Stainless Steel



Model
ST1D1T8



Model ST2D1T18

Enable A Quiet, Healing Environment

Features & Benefits

- Formed 1-piece ledge panel design eliminates seams and joints
- Friction cam ledge mounts eliminate vibration noise when full or empty
- Formed side panels minimize vibration noise
- Doors open 270° for unobstructed access.
- Pivot travel pressure latch eliminates door vibration during transport
- Pull-type door with magnetic closure and hold open with ergonomic full-height door grasp for easy opening
- Wide, cushion-tread casters are specifically engineered for noise reduction
- Front casters are offset for easy travel over uneven surfaces
- Tubular push handle
- Compartment floor with drain emboss base and plug for easy drainage
- Anti-static floor strap eliminates static buildup
- NSF listed

Warranty

- Two years parts and one year labor



Application

Lakeside **Stealth Series** tray carts are designed to be the industry's quietest, and are ideal for room service or traditional tray delivery operation. Noise reduction design helps improve CMS HCAHPS scores by providing a quiet, healing environment.

Specifications

The tray cart will be made up of 18-gauge Type 201 stainless steel welded and riveted construction to accommodate 14" x 18" or 15" x 20" trays. The top and base will be made of 16-gauge Type 201 stainless steel. Side panels will have noise reducing 5" wide folded channels running entire height of panel. The door(s) will be made of 20-gauge Type 201 stainless steel, double pan design, and will be mounted on stainless steel lift off hinges which allow 270° door swing. Door(s) will have magnetic closure with pivot transport latch. Door(s) will be held in fully open position by a magnet mounted on the cabinet exterior along with a magnetic catch plate mounted to the exterior of the door. Tray ledge panels will be of formed 1-piece design and will be removable for easy cleaning. Ledge panel mounts will be of friction cam design to eliminate vibration noise. Tray compartments will have vents on the end panels, and top will have tubular rail on three sides. Compartment(s) will have a drain emboss base with drain plug. Exterior base will have bottom corner bumpers. Casters will be 6" in diameter, rigid and swivel, fastened to an undercarriage of Type 201 stainless steel. Rigid casters will be offset to facilitate travel over uneven surfaces. Caster wheels will be 2" wide, with soft rounded tread to ensure a smooth and quiet ride on carpet or tile. Casters will have a 1/4" neoprene pad between mount plate and unit undercarriage to reduce floor vibration. Unit is NSF listed.


Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.


800-558-8565 • 414-902-6400 • Fax 414-902-6446 • info@eLakeside.com • www.eLakeside.com/foodservice

Stealth® Tray Delivery Carts

Stainless Steel



Model ST1D2T14



Model ST1D1T8


Model Information

Model	Pass-Through Model¹	Overall Size			Tray Capacity	Trays Per Ledge	Case Wt. Lbs.
W		L	H				
Single Compartment							
ST1D1T6	ST1DPT1T6	22¾"	25¼"	47¼"	6	1	170
ST1D1T8	ST1DPT1T8*	22¾"	25¼"	57¾"	8	1	190
ST1D2T10	ST1DPT2T10	27¾"	36¾"	42"	10	2	210
ST1D2T12	ST1DPT2T12	27¾"	36¾"	42"	12	2	230
ST1D2T14*	ST1DPT2T14*	29¾"	36¾"	53"	14	2	250
ST1D2T16*	ST1DPT2T16*	29¾"	36¾"	58"	16	2	270
ST1D2T18*	ST1DPT2T18*	29¾"	36¾"	63½"	18	2	290
ST1D2T20*	ST1DPT2T20*	29¾"	36¾"	68½"	20	2	310
Double Compartment							
ST2D1T10	ST2DPT1T10	41"	25½"	42"	10	1	230
ST2D1T14*	ST2DPT1T14*	43¼"	28¼"	53"	14	1	270
ST2D1T16*	ST2DPT1T16*	43¼"	28¼"	58¼"	16	1	290
ST2D1T18*	ST2DPT1T18*	43¼"	28¼"	63½"	18	1	310
ST2D1T20*	ST2DPT1T20*	43¼"	28¼"	68¾"	20	1	330
ST2D2T20	ST2DPT2T20	51¼"	36¾"	42"	20	2	350
ST2D2T24	ST2DPT2T24	51¼"	36¾"	47¼"	24	2	370
ST2D2T28*	ST2DPT2T28*	53¼"	36¾"	53"	28	2	390
ST2D2T32*	ST2DPT2T32*	53¼"	36¾"	58¼"	32	2	410
ST2D2T36*	ST2DPT2T36*	53¼"	36¾"	63½"	36	2	430

*Features recessed vertical push handles. ¹ Pass-through models feature doors on both sides of compartment.

Options:

- ☐ Custom tray size (Specify _____)
- ☐ Custom exterior graphics
- ☐ Custom ledge spacing (Specify _____)
- ☐ Fourth top rail
- ☐ 6" x 1" wide casters (Deduct)
- ☐ Brake casters (2 ea. swivel)
- ☐ Menu card holder
- ☐ Drain reservoir
- ☐ Perimeter bumper
- ☐ 8" casters (Double Compartment models only)



Formed One-Piece Ledge Panels



Friction cam ledge panel mounts eliminate vibration noise.



Pivot door travel latch holds door firmly against door frame pads.



Lakeside Manufacturing, Inc.
4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.
800-558-8565 • 414-902-6400 • Fax 414-902-6446
info@elakeside.com • www.elakeside.com/foodservice