

ELECTRIC BAIN-MARIE ON COMPARTMENT

Project:
Rev.:
Zone:
Location:



CODICE
CR0991249

MODELLO
D94/10CBE

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

Tank dimensions Gastro Norm. Perforated false bottom for vessel support. Adjustable temperatures from 30° to 90°C. Tank equipped with overflow level. Gas version: burner controlled by thermostatic safety thermocouple valves and piezo ignition. Electric version: armoured heating elements positioned outside the tank, water filling by means of solenoid valve.

Adjustable temperature in tank with overflow and perforated false bottom for supporting containers. GN-sized tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

ELECTRIC BAIN-MARIE ON COMPARTMENT

Project:
Rev:
Zone:
Location:



CODICE
CR0991249

MODELLO
D94/10CBE

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0991249
DEFINITION	D94/10 CBE BAIN-MARIE EL.M80 1/2 COMPARTMENT G.
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	57,000 Kg
VOLUME (net)	0,626
PACKAGE LENGTH	840,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1170,000 mm
PACKAGE VOLUME	1,003 m3
GROSS PACKING WEIGHT	72,000 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	5,400 kW
IP GRADE	IPX5
CERTIFIED MODEL	D94/10 CBE

ELECTRIC BAIN-MARIE ON COMPARTMENT

Project:
 Rev:
 Zone:
 Location:


CODICE
CR0991249

MODELLO
D94/10CBE

SERIE
DIAMANTE90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
 MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda

- E** Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief
 Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel
- S** Attacco scarico acqua - Wasserablauf - Water outlet
 Vidange de l'eau - Desaguadero - Wateraftapaansluiting
EN 10226-1 R 1/2
- H2O** Attacco arrivo acqua - Wasseranschluss - Water inlet
 Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 1/2

ELECTRIC BAIN-MARIE ON COMPARTMENT

Project:
Rev:
Zone:
Location:




CODICE
CR0991249

MODELLO
D94/10CBE

SERIE
DIAMANTE90

Product's PLUS



Adjustable temperature in tank with overflow and perforated false bottom for supporting containers. GN-sized tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

ELECTRIC BAIN-MARIE ON COMPARTMENT

Project:
Rev:
Zone:
Location:



CODICE
CR0991249

MODELLO
D94/10CBE

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0996979	DBVP4	
CR0997009	DBVPA4	
CR0997029	DAPC	
CR0997019	DAPD	
CR0997039	DAPS	
CR0997049	DAPM	
CR0997059	DAPDB	
CR1353589	DBVC4	
CR0592679	94/10 BH	Open base - hygienic finish H2 80cm series 90
CR1353569	DRG21	
CR0592799	ZF8	
CR0592830	ZG	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment