

Caribbean Blown Air Deck



Dimensions

Model ----- Top size ----- loading

CARIB72.912SY 1206 x 777 x 900mm 1.6kW

CARIB72.916SY 1606 x 777 x 900mm 2.1kW

CARIB72.919SY 1906 x 777 x 900mm 2.4kW

(970mm High to top of prep shelf)

Electrical Connection

220V/240V, 1 phase, 50 Hz.

Cable

2 metres with 13 amp plug fitted.

Designed to meet the EN ISO 23953 standard, providing M1 cabinet class conditions and exceeding the climate class 3 environment of 25°C at 60% RH.

In use the systems achieves a balanced air temperature throughout the cabinet of between 2°C & 5°C in ambient temperatures up to 27°C at a relative humidity of 50%. Maintains core product temperature below 5°C even during the defrost cycle. Features a raised rear preparation shelf compatible with the optional polyethylene chopping board. 1606 & 1906mm units have open ambient cupboards to the rear.

Well

Completely removable well giving easy access for cleaning and maintenance.

Load line indicator at 100mm to assist in the safe presentation of food.

304 Stainless steel well - 170mm deep.

Accepts GN1/1 gastronorm containers up to 100mm deep.

Gantries

Constructed from 50mm, bright polished stainless steel tube.

Fluorescent illumination to stainless steel light box.

Toughened glass screens.

Digital temperature control and readout.

Refrigeration system

Self-regulating condensate system.

R404a refrigerant.

Optional Extras:

Tray slides.

Kick plinths.

Plate shelves.

Glass mid shelves.

Polyethylene chopping board