

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

Standard Features

- 316 stainless kettle liner (up to 40 gallon, 304 40+ gallon)
- 304 stainless kettle jacket
- Kettle Protection System
- Thermostat temperature control, 150° F-260° F
- Pressure relief valve
- Air eliminator valve
- Pressure gauge
- Jacket-water fill and sight glass
- Automatic low water cutoff and indicator light
- Safety pilot control
- Full body insulation (3" - 14") between kettle jacket and outer casing
- Electronic ignition, 120V standard
- 304 stainless outer casing seam welded to the 3" reinforced radius lip
- 304 stainless, seam welded control console
- 304 stainless, reinforced gear box
- 304 stainless, seam welded tubular frame construction
- Self-locking, permanently lubricated, single reduction worm gear case
- Adjustable flanged feet

Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle\*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet\*
- Faucet bracket (ALFBST)
- Automatic water filling meter (ALACWS)
- Correctional Package\*
- 316 liner AL316LNR

\* Call AccuTemp for additional information

Electrical Options

120V, 208V, 240V

Short Spec

AccuTemp Edge Series gas powered tilting kettle, 2/3 jacketed, model ALTLGB-XX (20-80 gallon capacity). Seamless deep-drawn 316 kettle liner (up to 40 gallon, 304 40+ gallon) with integrally formed radius lip and 304 stainless steel kettle jacket, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator. Self-locking worm gear tilt mechanism, 2" tubular support frame. Tilting cut-off switch. Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 126°C). Adjustable flanged feet.

Other Approvals



Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Gas quick disconnect 1/2"\*
- Flexible gas hose 1/6" x 60" (ALTQDH)
- Draw off drain hose (ALDIH)
- Disc strainer; solid or perforated, 1/8" or 1/4"\*
- Measuring strip (ALMS)
- Lift-off cover (ALLCT-S (5-25 gal) OR ALLCT-M (30-60 gal))
- One piece actuator-assisted lid, 20-80 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)
- 2" or 3" draw off valve, compression or ball type fitting\*



Model ALTLGB-80 shown with optional draw off valve

Gal.	BTU RATING		Natural	Propane	Electrical
	Natural	Propane			
20	63,200	59,600	Supply Piping: 1/2" IPS	Supply Piping: 1/2" IPS	120 volt (standard) 208/240 volt (optional) 50/60 Hz 1 Phase 1 Amp
30	66,700	67,800			
40	79,900	83,100	Supply Piping: 3/4" IPS	Supply Piping: 3/4" IPS	
60	106,800	108,500	Supply Pressure: 5-7" W.C. (nominal)	Supply Pressure: 12-14" W.C. (nominal)	
80	131,400	131,100	Outlet Pressure Factory Setting: 3.5" W.C.	Outlet Pressure Factory Setting: 9.0" W.C.	

MODEL ALTLGB DIMENSIONS*													
Gal.	A	B	C	C1	D	F	G	H	K	L	S	T	XI
20	22.0	16.0	35.7	12.6	23.7	46.8	38.0	15.0	32.1	32.5	15.5	25.6	11.0
30	23.0	20.3	38.3	12.6	23.8	47.4	39.0	13.3	32.1	33.5	16.5	25.6	13.5
40	25.5	22.3	41.0	11.4	26.2	51.1	42.5	14.0	34.7	36.8	17.5	27.3	13.4
60	29.5	25.0	47.3	9.5	26.7	56.6	46.1	17.5	35.6	41.4	18.6	26.9	20.1
80	32.5	27.6	48.9	11.0	28.6	57.9	47.5	16.4	41.6	43.4	19.9	29.9	21.9

\*Drawing represents model ALTLGB with optional 3" draw-off valve. Dimensions on these drawings are applicable when using an optional 3" draw-off valve.

Unit is supplied with 6' cord with plug.

