

PROJECT:		
ITEM #		_ OTY:
MODEL #		
0522		
AIA #	SIS #	

SANDWICH PREP REFRIGERATOR WITH DRAWERS

VSPD72HC-30B-4



EXCLUSIVE WARRANTY

- **6 Year Parts & Labor Warranty**
- 7 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)













CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back and bottom)
- · Aluminum Interior
- · Hinged, Insulated Flat Lift Up-Lid
- · One-Piece, Snap-In Magnetic Door/Drawer Gaskets
- · Heavy-Duty Pan Liner
- · 8' Cord And Plug (see electrical data for details)

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- · Rear Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- **Epoxy Coated Evaporator Coil**
- Refrigerator Capable Of Maintaining Product Temperature

FEATURES

- · Full Electronic Control
- Low Profile Horizontal Door/Drawer Handles
- Cartridge Style Hinges
- Epoxy Coated Shelves (2 per section)
- Stay-Open Door/Drawer Feature For Easy Product Loading
- Top Accommodates Up To 6" Deep Food Service Pans With Locking Divider Bars
- · Heavy-Duty Stainless Steel Drawer Frames
- Telescoping Drawers Slides With Locking Mechanism
- Accommodates 6" Deep Food Service Pans In Both Upper And Lower Drawers (pans not included)
- 10" Cutting Board Constructed Of White Polyethylene Plastic
- 6" Casters Two With Brakes



OPTIONS & ACCESSORIES

- Secure-Temp™ Technology
- · Stainless Steel Interior
- · Stainless Steel Back
- · Door/Drawer Locks
- · Door Swing Orientation (at time of order)
- · Exterior Door Laminate

- · Garnish Rack (full & half pan)
- · Single Or Double Overshelf Kit
- · Silver Freeze Shelves (chrome style)
- · Shelf Divider
- · Front Or Side Crumb Catcher
- · 12" Cross Bar


- · Roll Top Cover
- · (1) 12 And (1) 18 Pan cover
- · 6" Legs Or 6" Seismic Legs
- · Casters: 3", Roller Kit, Low Profile
- · Correctional Package
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168


Rev. 10/6/23 Printed in U.S.A. APPROVAL: _ DATE: _




VSPD72HC-30B-4









We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	20.0	Cabinet Voltage	115/60/1	Height	49"	
Width, Overall (in.)	72"	Total Amperes	5.4	Width	75"	
Depth, Overall (with handle)	38 3/8"	NEMA Plug (8' cord)	5-15P	Depth	38"	
Height Overall (6" casters)	57 1/8"	REFRIGERATION DATA		Crated Weight	520 lbs	
Depth, Door Open 90°	52 1/4"	Condensing Unit Size, HP	1/3			
Drawer Openings (in.)	19 1/2" x 7 1/2" 19 1/2" x 11 1/8"	Refrigerant*	R-290	*NOTE: Remote units are field wired and come with 6' legs. Refrigerant must be specified at time of order.		
Door Opening (in.)	19 1/2" x 21 5/8"	Capacity (BTU/HR) (100°F/20°F)	2291			
No. Of Doors/Shelves/Drawers	1/2/4	Heat Rejection (BTU/HR)	3436.5			
No. Of Pans	30	Charge (lbs/grams)	0.2095/95			
Required Clearance: 3" Bottom & 2" Rear						

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 10/6/23 Printed in U.S.A.

