Reveal®

Refrigerated Service Slide In Counter Case

Structural Concepts®
DELIVERING FRESH. ALWAYS.™

- **NE3635RSV** 35-3/4"L x 33"D x 35-3/8"H
- **NE4835RSV** 47-3/4"L x 33"D x 35-3/8"H
- **NE6035RSV** 59-3/4"L x 33"D x 35-3/8"H
- **NE7235RSV** 71-3/4"L x 33"D x 35-3/8"H



NE4835RSV

Included

- NOTE: Glass warranty only applicable to first point of delivery
- Breeze~E (Type-II) self-contained refrigeration
- (3) Levels of clear glass shelving removable and adjustable on 1" centers
- Condensate pan (self-contained refrig. only)
- LED top & shelf lights
- NOTE: Overall case height is 54-3/4" (includes below counter)
- One piece formed ABS plastic tub
- One year parts & labor; 5 year compressor warranty
- Vertical, fixed front & side UV bonded frameless glass
- Warmest average product temperature of 40°F or less

Specify	Standard Features	Additional Options
FRAME EXTERIOR COLOR	• Powder coated Silversan Black	• Powder coated (stock/non-stock colors) • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• NOTE: Interior color must be FDA & NSF approved • Powder coated (stock colors, specify RAL#) • Stainless steel
BASE SUPPORT	• Casters (non-locking) w/ levelers (self-cont.)	• 6"H legs • Shims (remote)
LEFT END GLASS	• Glass end	• No end glass w/ synchronized defrost
RIGHT END GLASS	• Glass end	• No end glass w/ synchronized defrost
REAR DOORS	• Clear glass rear sliding doors	• Reflective glass rear sliding doors
LIGHTS	• LED 3500K w/ frosted lens	• LED 3000K w/ frosted lens • LED 4000K w/ frosted lens
ELECTRICAL CONNECTION	• 10' Straight blade power cord (self-cont.)	• 10' Locking power cord (self-cont.) • Electrical leads (remote)
CLEAN SWEEP	• None	• Clean Sweep® coil cleaner (self-cont.) (2 year parts & labor warranty included)
REAR VENTED PANEL	• None	• NOTE: Unit can intake & discharge from rear w/ optional rear vented panel • Powder coated (stock/non-stock colors) • Stainless steel
REFRIGERATION	• Breeze~E (Type-II) self-contained refrigeration (rear access)	• Breeze~E (Type-II) self-contained refrigeration (front access) (see important notes) [1] • Remote w/thermostat, solenoid & TXV (front access) [2] • Remote w/thermostat, solenoid & TXV (rear access)
MISCELLANEOUS		• Rear door lock • Second year parts & labor warranty (excludes compressor)

Option Notes: 1 - Read important notes for remote options
2 - Read important notes for remote options


Reveal®

Refrigerated Service Slide In Counter Case


Structural Concepts®
DELIVERING FRESH. ALWAYS.™


Intended Environment:	Type II - Designed to operate in ambient conditions of 80°F and 55% relative humidity unless noted otherwise in system information below.	
Zone	**Intended Product To Be Displayed**	**Warmest Avg Prod Temp ° F**
1	Unpackaged refrigerated products-Prechilled to Warmest Avg Prod Temp.	40

PLAN VIEW



SIDE VIEW





	"A"	"B"	"C"	"D"
NE3635RSV	8 1/2"	16 3/4"	8 1/2"	10 1/2"
NE4835RSV	8 1/2"	28 3/4"	8 1/2"	10 1/2"
NE6035RSV	8 1/2"	40 3/4"	8 1/2"	10 1/2"
NE7235RSV	8 1/2"	52 3/4"	8 1/2"	10 1/2"

	"M"	"N"
NE3635RSV	14 1/2"	32 5/8"
NE4835RSV	20 1/2"	32 5/8"
NE6035RSV	26 1/2"	32 5/8"
NE7235RSV	32 1/2"	32 5/8"

NOTES:
1. 11 3/8" TALL, FULL WIDTH OF CASE OPENING IN CABINET OR COUNTER IS REQUIRED TO PULL OUT REFRIGERATION SYSTEM.
2. SEE DESIGN GUIDE FOR CUTOUT SIZE IN CABINET FOR CASE TO DROP INTO.
3. BACK OF COUNTER / CABINET MUST BE VENTED PROPERLY FOR ADEQUATE AIRFLOW TO CONDENSER.
4. **REPRESENTS REAR PULLOUT REFRIGERATION. AIR FLOW INTAKE AND EXIT DETAILS ARE REVERSED WITH FRONT PULLOUT REFRIGERATION OPTION.
5. SELF-CONTAINED ACCESS ONLY BY PULLING OUT CONDENSER UNIT.
6. SEE "COUNTER INSTALLATION GUIDE" FOR AIR FLOW REQUIREMENTS.

NOTE: ALL DIMENSIONS APPROXIMATE

ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH ¾" OR 1½" PVC TUBE).
REFRIGERATION LINE CONNECTION.
REMOTE FLOOR SINK & UTILITIES ACCESS AREA.
SELF-CONTAINED CASE SERVICE ACCESS AREA.
DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications

Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
NE3635RSV	N/A	35.75	7.50	Remote (DX)	Circuit #1	110-120	1	60	1.08	38	2+G	Leads Single	20.00	1188	1100	700
				Remote (DX)	Circuit #1	110-120	1	60	1.08	38	2+G	Leads Single	20.00	1188	1100	
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	1.00	28	2+G	Leads Single	20.00	1188	1100	
				Self-Contained (R290)	Circuit #1	110-120	1	60	10.73	964	2+G	5-15P or L5-15P	N/A	N/A	N/A	
NE4835RSV	N/A	47.75	7.50	Remote (DX)	Circuit #1	110-120	1	60	1.08	44	2+G	Leads Single	20.00	1534	1420	1,000
				Remote (DX)	Circuit #1	110-120	1	60	1.08	44	2+G	Leads Single	20.00	1534	1420	
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	1.00	34	2+G	Leads Single	20.00	1534	1420	
				Self-Contained (R290)	Circuit #1	110-120	1	60	11.18	995	2+G	5-15P or L5-15P	N/A	N/A	N/A	
NE6035RSV	N/A	59.75	7.50	Remote (DX)	Circuit #1	110-120	1	60	1.38	64	2+G	Leads Single	24.00	1879	1740	1,100
				Remote (DX)	Circuit #1	110-120	1	60	1.38	64	2+G	Leads Single	24.00	1879	1740	
				Self-Contained (R290)	Circuit #1	110-120	1	60	11.18	1,005	2+G	5-15P or L5-15P	N/A	N/A	N/A	
NE7235RSV	N/A	71.75	7.50	Remote (DX)	Circuit #1	110-120	1	60	1.38	70	2+G	Leads Single	20.00	2203	2040	1,200
				Remote (DX)	Circuit #1	110-120	1	60	1.38	70	2+G	Leads Single	20.00	2203	2040	
				Remote (GLYCOL 35%)	Circuit #1	110-120	1	60	1.30	60	2+G	Leads Single	20.00	2203	2040	
				Self-Contained (R290)	Circuit #1	110-120	1	60	15.48	1,542	2+G	5-20P or L5-20P	N/A	N/A	N/A	

*** Does not include electric defrost on freezer models.

Regulatory Approvals:	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7

In Accordance with AHRI Std 1200

DOE 2017 Energy Efficiency Compliant

Important Notes:

1) REMOTE REFRIGERATION NOTE: Condensing unit not included, floor drain required.
2) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
3) Verify ventilation requirements for your installation by referring to the Design guide located in our Foodservice Resource Library at structuralconcepts.com.
4) Rear Access - Counter must be configured to allow air to be drawn in the rear and discharged out the front.
5) Front Access - Counter must be configured to allow air to be drawn in the front and discharged out the rear.
6) 19.25" minimum space required beneath counter surface.
7) Due to DOE regulations, the maximum counter height on this model is 30".
8) Glass warranty only applicable to first point of delivery.

⚠ **WARNING:** This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Placement of Case

Consider where the display case will be positioned relative to walls, ceilings, HVAC vents, windows, and other equipment discharging warm air.

The 5′ - 10′ - 15′ Rule

Stay 5′ away from an exterior window

Direct sunlight increases the heat load on the front of the display resulting in the refrigeration system having to work harder and possible condensation on the case.

Remain 10′ away from HVAC ceiling vents

Air blowing on the front of the display interrupts the air curtain and causes product temperatures to increase.

Minimum 4″ clearance to walls & ceilings.
Refer to spec sheets & design guide for further information.

With service display cases that have a glass front, air blowing on the front glass causes condensation to develop.

Position the display 15′ away from exterior doors

Air drafts from the front exterior doors interrupt the air curtain, allowing warm air to penetrate the inside of the display, affecting product temperature.

