

# ELECTRIC PASTA COOKER 1 BOWL 28 L

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0990049

MODELLO  
D72/10CPE

SERIE  
DIAMANTE70



## GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

## TECHNICAL SPECIFICATIONS

Safety pressure switch to prevent activation of heating without water in the tank.

Water loading by means of solenoid valve.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.

# ELECTRIC PASTA COOKER 1 BOWL 28 L

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0990049

MODELLO  
D72/10CPE

SERIE  
DIAMANTE70

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR0990049
DEFINITION	D72/10 CPE EL. COOKER M40 1V.28LT
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NET WEIGHT	38,000 Kg
VOLUME (net)	0,254
PACKAGE LENGTH	440,000 mm
PACKAGE WIDTH	850,000 mm
PACKAGING HEIGHT	1160,000 mm
PACKAGE VOLUME	0,435 m3
GROSS PACKING WEIGHT	47,000 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	5,670 kW
VOLTAGE	400
IP GRADE	IPX4
CERTIFIED MODEL	D72/10 CPE

# ELECTRIC PASTA COOKER 1 BOWL 28 L

Project: .....  
 Rev: .....  
 Zone: .....  
 Location: .....




CODICE  
CR0990049

MODELLO  
D72/10CPE

SERIE  
DIAMANTE70

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm  
 MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda

- H2O** Attacco arrivo acqua - Wasseranschluss - Water inlet  
 Arrivée eau - Union de agua - Wateraansluiting  
**EN ISO 228-1 G 3/4**
- E** Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief  
 Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel
- S** Attacco scarico acqua - Wasserablauf - Water outlet  
 Vidange de l'eau - Desaguadero - Wateraftapaansluiting  
**EN 10226-1 R 1**

# ELECTRIC PASTA COOKER 1 BOWL 28 L

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0990049

MODELLO  
D72/10CPE

SERIE  
DIAMANTE70

## Product's PLUS



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Safety pressure switch to prevent activation of heating without water in the tank.



Water loading by means of solenoid valve.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



# ELECTRIC PASTA COOKER 1 BOWL 28 L

Project: .....  
Rev: .....  
Zone: .....  
Location: .....



CODICE  
CR0990049

MODELLO  
D72/10CPE

SERIE  
DIAMANTE70

## ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0999079	CCP12	BASKET GN1/2 SIDE HANDLE
CR0999089	CCP13L	BASKET GN1/3 SIDE HANDLE
CR0999099	CCP13F	BASKET GN1/3 FRONT HANDLE
CR0999109	CCP16D	BASKET GN1/6 RIGHT-HAND HANDLE
CR0999119	CCP16S	BASKET GN1/6 LEFT HANDLE
CR0999129	CCP19	BASKET GN1/9 FRONT HANDLE
CR0999159	CVCP26	
CR0999229	7KIT-A	PASTA COOKER KIT
CR0999239	7KIT-B	PASTA COOKER KIT
CR0999249	7KIT-C	PASTA COOKER KIT
CR0592779	ZF4	
CR0592830	ZG	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0599649	7ZL	