

CA67 Non-Insulated Series Non-Insulated Economy Proof/Hold Cabinet

Our most economical unit accommodating sheet pans



- All aluminum construction with magnetic latch handle door
- Extruded interlocking aluminum side panels extend 9/16" and will support full (18" x 26") and half size (18" x 13") sheet pans (lip hung)
- Includes dual purpose HHP-SB-EXT-6 to use for proofing or holding
- Pan stop provides uniform heat distribution throughout
- Full height accommodates up to (33) 18" wide pans on 1-1/2" center spacing
- Ambient air temperature may affect heating performance
- Small Plate Series Casters - 5" POLU swivel, 2 w/brakes



**Interlocking
Extruded
Side Panels**

Bottom mount removable heat unit for easy maintenance and repair includes external cabinet controls



Digital thermometer in face of heat unit Temp adjustable to approximately 165°F in Hold for non-insulated cabinets



Hold provides dry heat only while Proof provides lower temps with humidity



Separate temperature and humidity controls

- 120 volt, 1700 watt, 60 cycle, single phase
- 8-foot cord with NEMA 5-20P plug
- Dedicated 20 amp circuit required



MODEL #	DOOR TYPE	CENTER SPACING	OUTSIDE DIMENSIONS H x W x D (INCHES)	SHEET PAN CAPACITY	WEIGHT (LBS.)
CA67-PF34-CD-R	CLEAR DOOR	1-1/2"	67-3/4 x 22-3/8 x 32-3/8	Up to 33	115
CA67-PF34-CDD-R	CLEAR DUTCH DOOR	1-1/2"	67-3/4 x 22-3/8 x 32-3/8	Up to 33	120
CA67-PF34-SD-R	SOLID DOOR	1-1/2"	67-3/4 x 22-3/8 x 32-3/8	Up to 33	114
CA67-PF34-SDD-R	SOLID DUTCH DOOR	1-1/2"	67-3/4 x 22-3/8 x 32-3/8	Up to 33	119
CA61-PF30-CD-R*	CLEAR DOOR	1-1/2"	61-7/8 x 22-3/8 x 32-3/8	Up to 29	105
CA61-PF30-SD-R*	SOLID DOOR	1-1/2"	61-7/8 x 22-3/8 x 32-3/8	Up to 29	103
CA55-PF26-CD-R*	CLEAR DOOR	1-1/2"	55-3/4 x 22-3/8 x 32-3/8	Up to 25	99
CA55-PF26-SD-R*	SOLID DOOR	1-1/2"	55-3/4 x 22-3/8 x 32-3/8	Up to 25	96
CA37-PF14-CD-R*	CLEAR DOOR	1-1/2"	37-3/4 x 22-3/8 x 32-3/8	Up to 13	89
CA37-PF14-SD-R*	SOLID DOOR	1-1/2"	37-3/4 x 22-3/8 x 32-3/8	Up to 13	87
CA31-PF10-CD-R*	CLEAR DOOR	1-1/2"	31-7/8 x 22-3/8 x 32-3/8	Up to 9	77
CA31-PF10-SD-R*	SOLID DOOR	1-1/2"	31-7/8 x 22-3/8 x 32-3/8	Up to 9	76

Options

- Bumpers
- Drip pan
- Push handle
- Hasp lock



Intertek



Intertek

(-R) Right hinge is standard, indicate -L for left hinge. *Left hinge and/or cabinets less than full height are non-returnable.

Proudly Manufactured in Michigan

www.lockwoodusa.com • customerservice@lockwoodusa.com

