



ELECTRIC

ELECTRIC COUNTERTOP | GRIDDLES


IMPERIAL



ITG-36-E

Model Numbers

ITG-24-E
ITG-36-E*
ITG-48-E*
ITG-60-E*
ITG-72-E*



STAINLESS STEEL GREASE
GUTTER AND 1 GAL (3.8 L)
GREASE CAN.



ELEMENTS LOCATED DIRECTLY
UNDER GRIDDLE PLATE FOR
EVEN HEATING.

ELECTRIC ELEMENT

- Thermostat maintains selected temperature during peak hours.
- 4 KW serpentine elements located under entire griddle plate.
- Maximum temperature is 550°

GRIDDLE PLATE

- Thick, highly polished steel plate holds temperature and has a quick recovery.
- Full 24" (610 mm) plate depth for more cooking surface.
- Surface is ideal for a large range of menu items.
- Optional chrome griddle top is available as an option.

GREASE MAINTENANCE

- Stainless steel grease gutter is 4" (102 mm) wide.
- Large 1 gal (3.8 L) capacity grease can has a weep hole to indicate when full.
- Grease can removes easily.

EXTERIOR FEATURES

- Stainless steel front, sides, splash guard, and ledge.
- Stainless steel ledge is one piece rolled for cleaning convenience.
- Range match profile when placed on a refrigerated base or equipment stand.
- Control knobs are constructed of virtually unbreakable plastic.
- 4" (102 mm) stainless steel legs are included.
- One year parts and labor warranty.



* Items ITG-36-E;
ITG-48-E; ITG-60-E
and ITG-72-E are
ENERGY STAR®
certified

IMPERIAL




1128 Sherborn Street, Corona, CA 92879 | 800.343.7790 | imperialrange.com | Imperialsales@imperialrange.com | imperialrange.com

© 2026 Imperial Cooking Equipment. Imperial reserves the right to change specifications at any time without prior notice and without any obligation for past or future equipment purchases. Visit www.imperialrange.com for specification updates.



ELECTRIC

ELECTRIC COUNTERTOP | GRIDDLES



ELECTRIC THERMOSTATICALLY CONTROLLED GRIDDLES

MODEL	WIDTH INCHES (MM)	NUMBER OF ELEMENTS	SHIP WEIGHT	
			KG	LBS
ITG-24-E	24" (610 MM)	2	136	300
ITG-36-E*	36" (914 MM)	3	195	430
ITG-48-E*	48" (1219 MM)	4	261	575
ITG-60-E*	60" (1524 MM)	5	328	725
ITG-72-E*	72" (1829 MM)	6	396	875

MODEL	GRIDDLE PLATE DIMENSIONS	DIMENSIONS	CRATED DIMENSIONS
ITG-24-E	24" W X 24" D (610 X 610)	24" W X 31" D X 14" H (610 X 787 X 356 MM)	26-1/2" W X 36" D X 16-1/2" H (673 X 914 X 419 MM)
ITG-36-E*	36" W X 24" D (914 X 610 MM)	36" W X 31" D X 14" H (914 X 787 X 356 MM)	38-1/2" W X 36" D X 16-1/2" H (978 X 914 X 419 MM)
ITG-48-E*	48" W X 24" D (1219 X 610 MM)	48" W X 31" D X 14" H (1219 X 787 X 356 MM)	50-1/2" W X 36" D X 16-1/2" H (1283 X 914 X 419 MM)
ITG-60-E*	60" W X 24" D (1524 X 610 MM)	60" W X 31" D X 14" H (1524 X 787 X 356 MM)	62-1/2" W X 36" D X 16-1/2" H (1588 X 914 X 419 MM)
ITG-72-E*	72" W X 24" D (1829 X 610 MM)	72" W X 31" D X 14" H (1829 X 787 X 356 MM)	74-1/2" W X 36" D X 16-1/2" H (1892 X 914 X 419 MM)

CLEARANCE REQUIREMENTS

For use only on non-combustible surfaces. Provide
0" clearance from non-combustible surfaces and
6" (152 mm) from combustible surfaces

OPTIONS AND ACCESSORIES

- Stainless steel equipment stands
- 6" (152 mm) casters for equipment stands
- 5" (127 mm) deep, stainless steel front landing ledge
- 7" (178 mm) deep, stainless steel front landing ledge
- Chrome griddle top, (add "-CG" to model number)
- Extra grease can



AMPERAGE REQUIREMENTS				
MODEL	TOTAL KW	VOLTS	PH	AMPS
ITG-24-E	8	208	3	34
	8	240	3	29
	8	480	3	15
ITG-36-E*	12	208	3	34
	12	240	3	29
	12	480	3	15
ITG-48-E*	16	208	3	67
	16	240	3	58
	16	480	3	29

AMPERAGE REQUIREMENTS					
MODEL	TOTAL KW	VOLTS	PH	AMPS J-BOX	
				A	B
ITG-60-E*	20	208	3	34	29
	20	240	3	29	25
	20	480	3	15	13
ITG-72-E*	24	208	3	34	34
	24	240	3	29	29
	24	480	3	15	15



* Items ITG-36-E;
ITG-48-E; ITG-60-E and
ITG-72-E are ENERGY
STAR® certified