

FFTSvg 7531

Freezing counter with dynamic cooling

Smart
Monitoring

Gross/net capacity	440/273 l
Ext. dimensions in mm (w/d/h)	1780/700/810
Int. dimensions in mm (w/d/h)	1320/550/570
Energy efficiency class	
Energy consumption in 365 days	2892 kWh
Climate class (energy directive)	5
Temperature class (energy directive)	L1
Climate class (safety standard)	5
Ambient temperature range	+10 °C to +40 °C ¹
Refrigerant	R 290
Noise output	63 dB(A)
Connection Rating	3.9 A
Frequency / voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	-10 °C to -20 °C
Housing material/colour	Chrome-nickel steel (1.4301 / AISI 304) / stainless steel
Door material	Chrome-nickel steel (1.4301 / AISI 304)
Liner Material	Chrome-nickel steel (1.4301 / AISI 304)
Type of Control	LED 7-segment display with buttons
Temperature display	external digital
Alarm in case of malfunction	visual
Compartment 1	door
Compartment 2	door
Compartment 3	door
Worktop	with worktop
Connectivity type	SmartCoolingHub
Connectivity solution	retrofittable
Interface	RS485 (optional)
Adjustable Shelving	6
Shelf material	wire shelves plastic-coated
Shelf loading	30 kg
Height of adjustable legs	100 – 150 mm
Handle	full-length integrated handle
Castors	swivel castors
Self-closing door	yes
Door hinges	left hand / right hand
Gross/net weight	177/155 kg
EAN-Nr.	9005382277973

¹ Indicates the ambient temperature at which the device can be operated safely.