

Flexiline



Recessed top hot cupboard - BS30HR

BS30HR

Compact recessed top hot cupboard specifically developed for the primary school meal service, where throughput is high and serving period short. Up to three electrically heated units can be linked together to operate from a single 13 amp socket. Specify height: 800, 825, 850 or 875mm and electrical handing left or right at time of order. Model No: BS30HR - 616mm wide unit. Model No: BS31HR - 518mm wide unit. Picture shows BS30HR unit finished in Heritage Green P.C.S. with optional TSS30D tray slide

Specifications

Dimensions: **BS30HR** External: 1200 x 616 x either 800, 825, 850, or 875mm Internal: 980 x 545 x height - 525mm **BS31HR** External: 1200 x 518 x either 800, 825, 850, or 875mm Internal: 980 x 447 x height - 525mm

Electrical Connection 220V/240V 1 phase 50Hz 1kW loading 4.1Amps approx Cable: 2 metres with 13 amp plug fitted RCD 13 amp socket for connecting adjoining unit.

Steel, Exterior: Stainless Steel, or plastic coated steel, Interior: Galvanised Steel.

Construction

Top: Stainless

Features

Standard Features:

- Extended stainless steel tops to both ends enables a continuous servery to be formed.
- On/off thermostat control to hot cupboard
- Double skin fully insulated construction reducing heat loss for safe & efficient operation.
- Fully GN1/1 gastronorm compatible. (not BS31HR - 518mm wide unit)
- Three removable shelves & supports.
- Removable element cover to maximise access for cleaning.
- Robust push/pull bar to both ends
- Removable sliding doors.
- Four x 100mm swivel castors two braked.

Options

- [Quartz heated gantry](#)
- [Trayslide](#)
- [Choice of colour finish](#)
- Left or right handed cable exit and interconnecting

Victor Manufacturing Limited

Lonsdale Works, Gibson Street, Bradford, BD3 9TF, West Yorkshire, England
Tel: +44 (0)1274 722125 Email: email@victormanufacturing.co.uk
Copyright © 2014 Victor Manufacturing Limited