F2A-HGE

Two Section Half Glass Door Freezer

F2A-HGE
11/03/26
Item # 13531E

W x D x H
55” x 33.5” x 79.5”*
*with 4” casters

Item #: _____
Project: _____
Qty: _____
AIA#: _____



Features

- **Maximum interior storage capacity with smallest external footprint**
- **Stainless steel interior with stainless steel exterior front, sides and top**
- **Unique ducted air distribution system**
- Energy efficient interior LED light
- Environmentally friendly R290 hydrocarbon refrigerant
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Cabinet walls are insulated with 2-3/8” of CFC free, foamed in place polyurethane
- Glass doors are energy efficient multi pane, argon filled
- Stainless steel/glass exterior doors come standard with locks
- Spring assisted self-closing doors with stay open feature
- Sturdy 8 gauge stainless steel hinge plate with welded hinge pin
- Extruded aluminum flush mount door handle
- Field reversible doors
- Evaporator coils are epoxy electrocoated (E-Coat) to help fight corrosion
- Energy efficient automatic hot gas condensate evaporator
- Top mount refrigeration comes standard with a condenser filter
- Stainless steel shelf supports
- (3) epoxy coated wire shelves are standard
- Center shelves for added storage capacity
- Standard with 4” casters (two with brakes)
- Stackable (two units high) to conserve warehouse floor space
- 10 ft. cord and plug

Dimensions / Capacity	Two Section F2A-HGE
Interior Storage Capacity (CF) (AHAM)	50.37 ft³
Overall Width x Depth	55” x 33.5”
Height (including 4” casters)	79.5”
Door Opening Width x Height	21.75” x 27.75”
Depth with Door Open at 90º	57”
Adjustable Shelves	6
Shelf Dimensions (W x D)	21.25” x 26”
Adjustable Center Shelves	3
Center Shelf Dimensions (WxD)	6” x 17.8”
Crated Shipping Weight	602 lbs
Crated Length x Width x Height	58” x 37.5” x 81”

Electrical / Refrigeration	Two Section F2A-HGE
Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P
Voltage Range	104-126
Ambient Temp. Range	45° to 100°F
Control Setpoint Range	-10° to +12°F
Amperage	9.1
Energy Consumption (kWh/day) @ASHRAE	16.30
Heat Rejection (BTU/Hr.) @NSF	1694
Approx. Nominal Compres. BTU/HR (HP)	2220(1HP)
Refrigerant / Charge Amount (oz)	R290 / (3.8 oz)

Options

- ☐ Additional epoxy shelves (HS-5052)
- ☐ Stainless steel shelves (HS-5054)
- ☐ Add’tl center epoxy shelves (HS-3509)
- ☐ Add’tl center stainless shelves (HS-3504)
- ☐ 6” Adjustable legs (HS-3546)
- ☐ Condensate pan (HS-5462)
- ☐ Tray/Pan slides (HS-3557)
- Foot pedals: (left hinge HS-5378) (right hinge HS-5379)

Seven year warranty on labor, parts, and compressor. Valid in United States, Canada, Puerto Rico and U.S. Territories.

For more information, please visit hoshizakiamerica.com/support/warranty/

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle


Hoshizaki reserves the right to change specifications without notice.

F2A-HGE


Two Section Half Glass Door Freezer

F2A-HGE
11/03/26
Item # 13531E


FRONT VIEW



SIDE VIEW



PLAN VIEW



Cabinet Construction

The exterior cabinet front, sides, and top are constructed of high quality stainless steel.The exterior back, and bottom are constructed of coated steel. The cabinet interior is constructed of stainless steel with a unique ducted air flow system. Three (3) heavy duty epoxy coated shelves per section are standard. Mounted on stainless steel pilasters shelves are adjustable in 1” increments. Cabinet walls are insulated with 2-3/8” of environmentally friendly, CFC free, foamed in place polyurethane. Perimeter and mullion heaters prevent condensation from forming on the face of the cabinet. Two interior LED light strips are mounted vertically and controlled by a separate switch on the controller. 4” polyolefin, casters (two with brakes) are standard.

Door Construction

Doors are constructed of a high grade stainless steel exterior with energy-efficient multi-pane, argon filled glass. Locks are standard. Doors are provided with a one piece, full length extruded aluminum flush mount handle and are mounted on eight (8) gauge stainless steel hinge plates with a welded hinge pin. Spring assisted self-closing doors are equipped with a stay open feature past 90 degrees. Snap-in magnetic door gaskets are easily removed for cleaning. Door hinging is field reversible.

Refrigeration System

The high efficiency refrigeration system is self-contained with an epoxy electrocoated (E-Coat) evaporator for extended life. Top mounted refrigeration system is easily accessible for service and includes a condenser filter with easy access from the top of the unit. The refrigeration system components are assembled on a high density expanded polypropylene platform that is removable from the main unit. A unique ducted air flow system achieves uniform air distribution within the cabinet to eliminate hot spots. Condensate removal is accomplished with a top mounted energy efficient non-electric evaporation system. A capillary tube controls the flow of environmentally friendly R290 refrigerant through the evaporator.Refrigeration system utilizes a time initiated heated defrost to eliminate any ice on the evaporator coil. Solid state digital controls monitor the operation and performance of the refrigeration system. The controls also provide visual high and low temperature and high and low voltage alarms. A LED display shows the cabinet temperature and is adjustable to Fahrenheit or Celsius. 115 volt units are equipped with a ten foot cord and plug (20.0 amps or less).

© HOSHIZAKI AMERICA, INC. 618 Hwy, 74 S., Peachtree City, GA 30269 | TEL 800-438-6087 | FAX 800-345-1325 | www.hoshizakiamerica.com