



GS4/C - Silverlink 600 Electric Counter-top Griddle - Chrome Plate - W 450 mm - 2.7 kW

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down.

- ✓ Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- ✓ Transfers heat to food more efficiently than a standard griddle
- ✓ Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- ✓ Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- ✓ The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

Specifications

Summary

| | |
|-----------------------------|-----------------------------------|
| Range Name | Silverlink 600 |
| Power Type | Electric |
| Unit Type | Counter-top |
| Available in UK Only | No |
| UK Warranty | 2 Years Parts and Labour Warranty |
| Export Warranty | Contact your local dealer |
| GTIN Code | 5056105100126 |

Power and Performance

| | |
|--|------------|
| Total Power kW | 2.7 |
| Temperature Range °C | 50-250 |
| IP Rating | IP33 |
| Cooking Area (Width x Depth) mm | 412 x 405 |
| Temperature Control | Mechanical |

Key Specifications

| | |
|---------------------------------|--------|
| Number of Heat Zones | 2 |
| Grill Plate Surface Type | Smooth |
| Grill Plate Material | Chrome |

Weights and Dimensions

| | |
|----------------------------------|-----|
| Unit Height (External) mm | 330 |
| Unit Width (External) mm | 450 |
| Unit Depth (External) mm | 600 |
| Net Weight Kg | 32 |

Supply Connections

| | |
|---------------------------------------|-------|
| Requires Installation | No |
| Requires Electrical Supply | Yes |
| UK 3 Pin Plug | Yes |
| Requires Hardwiring | No |
| Electrical Supply Rating Watts | 2,700 |
| Single Phase Amps | 11.7 |
| Single Phase Voltage | 230 |
| Three Phase Voltage | 400 |




Shipping

| | |
|-------------------------|------|
| Packed Weight Kg | 43 |
| Packed Height cm | 63.5 |
| Packed Width cm | 70 |
| Packed Depth cm | 55 |

Available Accessories

| | |
|-------------|--|
| CC4 | Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 450 mm |
| CN4 | Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm |
| HC4 | Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 450 mm - 0.5 kW |
| HCL4 | Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 450 mm - 0.5 kW |
| SB4 | 450 GRIDDLE SPLASHB |
| SLS4 | Silverlink 600 Free-standing Floor Stand - for units W 450 mm |

Technical Picture



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm