

GAS FRYER 1 BOWL 17 L

Project:
Rev:
Zone:
Location:



CODICE
CR1353709

MODELLO
D9217/10 FRIG

SERIE
DIAMANTE90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

AISI 18/10 stainless steel tanks with cold zone and foam expansion zone.
Oil drain taps.
Oil drip pans on request.
Safety thermostat (230°C) against excessive oil temperatures.
IPX5 water jet protection

Tank depth and width increased to increase capacity.

Moulded basin with flat top and large cold zone for easy cleaning.

The large cold zone allows frying residues to settle, significantly extending the quality and life of the oil.

Heating via stainless steel burner outside the tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

GAS FRYER 1 BOWL 17 L

Project:
Rev:
Zone:
Location:



CODICE
CR1353709

MODELLO
D9217/10 FRIG

SERIE
DIAMANTE90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1353709
DEFINITION	D9217/10 FRG GAS FRYER M40 1V17LT
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	55,000 Kg
VOLUME (net)	0,313
PACKAGE LENGTH	440,000 mm
PACKAGE WIDTH	1020,000 mm
PACKAGING HEIGHT	1160,000 mm
PACKAGE VOLUME	0,522 m3
GROSS PACKING WEIGHT	65,000 Kg
GAS POWER	13,00
GAS POWER (G25.3/25mbar)	13,00
CERTIFIED MODEL	D9217/10 FRIG

GAS FRYER 1 BOWL 17 L


Project:
 Rev:
 Zone:
 Location:

CODICE
CR1353709

MODELLO
D9217/10 FRIG

SERIE
DIAMANTE90

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
 MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwattel - Entrada cabo eléctrico	G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasansluiting - Ligação gás EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água
S1 Scarico vasca - Wannababflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno A2 = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio
S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukklep - Válvula de depressão	
S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmita com Sistema de aquecimento indirecto	
S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno	L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nivel

GAS FRYER 1 BOWL 17 L

Project:
Rev:
Zone:
Location:



CODICE
CR1353709

MODELLO
D9217/10 FRIG

SERIE
DIAMANTE90

Product's PLUS



Heating via stainless steel burner outside the tank.

Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.




Tank depth and width increased to increase capacity.



Moulded basin with flat top and large cold zone for easy cleaning.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



The large cold zone allows frying residues to settle, significantly extending the quality and life of the oil.

GAS FRYER 1 BOWL 17 L

Project:
Rev:
Zone:
Location:



CODICE
CR1353709

MODELLO
D9217/10 FRIG

SERIE
DIAMANTE90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1353879	DCF15/17	Basket for tub 15 - 17 litres 1 pcs 24x33,7x12 cm capacity 15-17 litres
CR1353889	DCF15/17P	Small basket for tub 15-17 litres 1 pcs 12x33,7x12 cm capacity 15-17 litres
CR1353929	D9BRO	
BN0221100047	CA 40/10	
BN0221100048	CA 60/10	
CR0592779	ZF4	
CR0592830	ZG	
CR0592820	9ZL	
MA97432000	R	
MA97433000	RI	
CR0592869	PZM	
CR0593580	9PT	
CR0592879	KPA	
CR0592940	9CAT *	Water column for top equipment