



GLASSWASHER GP-50 230/50/1 DD

Rack size 500x500mm and door clearance 260 mm



1303162



- ✓ Easy access to components for repair.

INCLUDES

- ✓ Peristaltic Detergent Pump

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Maximum glass height: 260 mm

Cycle duration: 90 " / 120 " / -- "
Production baskets/hour: 45 / 30 / --

Boiler capacity: 4.5 l
Wash tank capacity: 23 l
Water consumption/cycle: 2.7 l

Loading

- ✓ Pump: 500 W / 0.75 Hp
- ✓ Tank: 1800 W
- ✓ Boiler: 2500 W
- ✓ Total loading: 3000 W

Electrical supply: 230 V / 50 Hz / 1 ~ (13 A)

External dimensions (WxDxH)

- ✓ Width: 580 mm
- ✓ Depth: 630 mm
- ✓ Height: 710 mm

Net weight: 52 Kg
Noise level (1m.): -- dB(A)

ACCESSORIES

- ☐ Stands for glass- and dishwashers
- ☐ Inserts & supplements
- ☐ Manual water softeners
- ☐ High Feet Kit
- ☐ Automatic water softeners
- ☐ Reverse Osmosis device OS-140P
- ☐ 500 x 500 mm. baskets

SALES DESCRIPTION

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ Upper and lower washing.
- ✓ Construction in stainless steel AISI 304 2B.
- ✓ Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

- ✓ Maximum protection of the washing pump.

Double-walled door

- ✓ Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

- ✓ GP Xperience: simple and intuitive use.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Electronic control panel with IP65 humidity protection.
- ✓ 100% Tested.

Tech-friendly

- ✓ Tool-free extraction of diffusers and filters for maintenance and cleaning



www.sammic.co.uk

Food Service Equipment Manufacturer
Unit 2, Trevanah Road
Troon Industrial Park
LE4 9LS - Leicester
uksales@sammic.com
Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

WARE WASHING
COMMERCIAL GLASSWASHER - GLASS-PRO LINE

product sheet
updated 01/10/2021