

Induced Energy




SLR-CS3000G-1 2 x 3KW Drop-in Remote Induction Hob

Induction Power Control Box


Front View - Induction Engines



Rear View



Coil Tray (Ceran Glass removed)



Coil Tray Ventilation Connection

Folding Grab Handle (1 each side)

Coil Out - Control Lead Fixing Bracket (optional)



Control Panel

Product Specifications

Maximum Power	7KW
Electrical Supply	32-amp single phase LN&E 50Hz (or 60Hz*) 230V *50Hz or 60 Hz to be specified at time of order
Cord	Standard cord length 2.5m, bespoke lengths to be specified at time of order
Plugs	3-pin 32-amp Commando type plug fitted (Blue) None UK appropriate plugs for each export market fitted
Weights	Coil Tray 5kg, Induction Control Box 14.4kg
Dimensions	Coil Box: 340 x 610 x 30mm extends to 200mm for power cord Induction Control Box: 300 x 400* x 320mm. Allow 500mm clearance for rear cables/air vent
Construction	Ceran top, stainless steel casing
Depth of Field	Up to 30mm
Safety Feature	Pan detection; boil-dry protection; overheat prevention; clean filter warning
User Interface	Display panel; clean filter warning; no pan present warning; glass hot warning; shutdown
Controls	2 x ergonomically designed knobs with precise setting of 1 to 99
Installation	Instructions provided
Cooling	Coil Box – blown ambient air ducted mechanically from control box Control Box – integral fan with removable air filter
Bespoke Options	Ceran top design/logo – minimum quantity 50
Warranty	2 years parts and labour, excluding case, Ceran top
CE	Approved

Induced Energy Limited operates a continuous programme of product development and improvement. Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants. NN13 7EB
Tel: 01280 705 900 Email:sales@inducedenergy.com

