



**SGF-25**



**SGF-50**

<i>Lids</i>	<b>1</b>	<b>2</b>
<b>Exterior Dimensions (L x D x H)</b>	<b>26 <math>\frac{3}{8}</math> x 26 <math>\frac{5}{8}</math> x 34 <math>\frac{1}{4}</math></b>	<b>49 <math>\frac{1}{2}</math> x 26 <math>\frac{5}{8}</math> x 34 <math>\frac{1}{4}</math></b>
<b>Capacity:</b>		
10 oz. Steins	85	240
8"(204 mm) Mugs	90	250
<b>HP</b>	<b>1/3</b>	<b>1/2</b>
<b>Voltage</b>	<b>115/60/1</b>	<b>115/60/1</b>
<b>Amps</b>	<b>8.5</b>	<b>9.6</b>
<b>Nema Config</b>	<b>5-15P</b>	<b>5-15P</b>
<b>Crated/Uncrated Weight</b>	<b>176/143 lb</b>	<b>354/299 lb</b>

- Exteriors include attractive wear-resistant vinyl on steel in black finish with stainless steel top
- Interior: 304 stainless steel floors with smooth white finish on interior sides
- Aluminum coated interior metal and epoxy coated steel wire adjustable dividers
- Oversized, factory balanced, refrigeration system holds 0°F (-17.7°C)
- NSF-7 approved for packaged and bottled product
- Guided airflow cools bottles on top first
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Condensing units slides out for easy maintenance
- Large storage capacity to meet the supply and demand

\* Specifications subject to change without notice

