TRUE MANUFACTURING CO., INC. • U.S.A. FOODSERVICE DIVISION • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434
ph. 636.240.2400 • toll free 800.325.6152 • fax 636.272.2408 • parts fax 636.272.9471 • www.truemfg.com

| Project Name | Location | | AIA # |
|---|---|---|---|
| Item # | Qty | Model # | SIS # |

# SPEC SERIES®

ROLL-IN SOLID SWING DOOR REFRIGERATOR

| models | STR1RRI-1S | STA1RRI-1S | STG1RRI-1S |
|---|---|---|---|



## STR1RRI-1S

| | |
|---|---|
| **Exterior** | Stainless steel door, front & sides. |
| **Interior** | Stainless steel side walls, back, floor, door liner, & ceiling. |


## STA1RRI-1S

| | |
|---|---|
| **Exterior** | Stainless steel door, front & sides. |
| **Interior** | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |

## STG1RRI-1S

| | |
|---|---|
| **Exterior** | Stainless steel door, with matching aluminum sides. |
| **Interior** | Aluminum side walls & back.<br>Stainless steel floor & ceiling. |


## plan view




ELEVATION




RIGHT VIEW




PLAN VIEW

## SPECIFICATIONS

| Dimensions | in. | mm. |
|---|---|---|
| Length | 35 | 889 |
| Depth | 34¾ | 883 |
| Height | 83¾ | 2128 |
| **Electrical** | **U.S.** | **International** |
| Horsepower | ⅓ | N/A |
| Amps | 8.9 | N/A |
| Voltage | 115/60/1 | |
| NEMA | 5-15P | |
| Cord Length | 9 ft. | 2.74 M. |

115/60/1
NEMA-5-15R

† Depth does not include 4¼" (108 mm) for ramp.
* Height does not include 1" (26 mm) for system mechanical components.

Specifications subject to change without notice.
Chart dimensions are roundedup to the nearest ⅛" (millimeters rounded up to the next whole number).

MADE WITH INNOVATION IN THE USA



Approvals

Available at

TRUE MANUFACTURING CO., INC. • U.S.A. FOODSERVICE DIVISION • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434
ph. 636.240.2400 • toll free 800.325.6152 • fax 636.272.2408 • parts fax 636.272.9471 • www.truemfg.com

| Project Name | Location | | AIA # |
|---|---|---|---|
| Item # | Qty | Model # | SIS # |

# SPEC SERIES®

ROLL-IN SOLID SWING DOOR REFRIGERATOR

| models | STR1RRI-1S | STA1RRI-1S | STG1RRI-1S |
|---|---|---|---|



## standard features

### REFRIGERATION SYSTEM

- Factory engineered, self-contained, expansion valve (TXV) system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True roll-in's a more efficient low velocity, high volume airflow design. This unique design ensures faster temperature recovery and shorter run times in the busiest of foodservice environments.
- Top mounted refrigeration system with evaporator positioned out of food zone to maximize capacity.

### CABINET CONSTRUCTION

- Insulation - Entire cabinet structure and solid door are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- One (1) heavy gauge stainless steel ramp.
- Designed to accept roll-in racks (inboard castors) with maximum dimensions of 27"L x 29"D x 66"H (686 mm x 737 mm x 1677 mm)(supplied by others).

### DOOR

- Lifetime guaranteed bolt style door lock standard.
- Door lock standard.
- Lifetime guaranteed heavy duty all metal working door handle.
- Positive seal self-closing door with 120° stay open feature. Lifetime guaranteed external cam lift door hinges, Three (3) per door section.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- Field reversible hinge.

### LIGHTING

- Incandescent interior lighting, safety shielded.

### MODEL FEATURES

- Exterior digital temperature display, available with either °F or °C .
- Evaporator epoxy coated to eliminate the potential of corrosion
- Interior bumpers protect cabinet walls from abuse caused by roll-in carts.
- NSF-7 compliant for open food product.

### ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.

### OPTIONAL FEATURES/ ACCESSORIES

***(upcharge & lead times may apply)***

- Stainless back. (STR, STA, STG)

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

| KCL | Model | Elevation | Right | Plan | 3D | Back |
|---|---|---|---|---|---|---|
| | ST( )1RRI-1S | | | | | |