

Product data sheet — Electric charrill 2

MKN-No.:
10018145

Cooking appliance according to DIN 18852 for application in the commercial preparation of food in the general catering industry, front cooking, free flow systems and snack bars. For cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 30 mm at the front and bent upwards 20 mm at the rear. Designed as a drip edge at the front. 50 mm cover projection closed to the appliance body.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Embossing behind the control knobs, ergonomically shaped knobs for a easy identification of the position.

Effective area:

Basin completely of CNS (1.4301) (AISI 304) welded seamlessly and greaseproof. Grill surface with cast iron grate, two separately adjustable heating zones.

Installation:

Equipped for installation of a 580 mm high Counter SL lower section with removable appliance feet (150 mm high) which are adjustable in height.

Type of energy:

Appliance completely electrically wired inside. All contactors required for operation are installed. Power supply cable with CEE plug connector.

Special feature:

Heating:

Heating by radiant tubular heating elements CNS/stainless steel with low surface load for long durability of the heating elements. For easy cleaning the heating elements can be completely swung out, with turning lever, locking device and swivel angle limit switch. Infinitely variable adjustment of the heating output via a power control switch for each heating zone respectively. Integrated appliance switch. Power contactor installed.



Product data sheet – Electric charrill 2

MKN-No.:
10018145

Cooking appliance for cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.

Current drawings you will find here:
www.mkn.com
▶ Partner Login
▶ spare parts database & download

Further features

- connection, sealing by means of connecting method – clamp bar is rounded (R 20) at the back for easier cleaning
- grill surface with three-part cast iron grate
- 2 separately adjustable heating zones
- pan can be filled with water for easy cleaning
- welded drain valve DN 20 at the front – with key confirmation for safe discharge
- mains connection cable with 5-channel CEE plug 16 A

Technical data

Dimensions (LxWxH*) (mm):	800 x 700 x 270
Effective area:	3
Dim.: effect. area (LxWxH) (mm):	580 x 470 x
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	10,5
Voltage ¹ (V):	400 3 NPE AC
Recommended fuses (A):	3 x 16
Frequency range (Hz):	50/60
Rated heat load (kW):	
Standard gas pressure – natural gas ² (mbar):	
Standard gas pressure – liquid gas ² (mbar):	
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	
Gross weight ³ (kg):	
Heat emission latent (W):	1838
Heat emission sensitive (W):	8400
Type of protection:	IPX4

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- CEE socket 16 A

Option / accessories

MKN-Artikelnr: Beschreibung:

¹ special voltages on request

² further types of gas on request

³ seaworthy packing on request

