

SPG415UK

Product Family	Dishwasher
Subfamily	Undercounter glasswasher
Basket dimensions	400x400 mm
Panel	Easyline 2016
Filter	5-stages filter system
Rinse pump with H.T.R. system	Rinse pump with atmospheric boiler
Dual Heating function	Yes
Usable load height	315 mm
Default power supply	230 V~ / 13 A / 2,9 kW / 50 Hz (NC)
Depth with door open	930 mm
Maximum plate diameter	300 mm
Maximum glass height	300 mm
Dimensions	460x600x705 mm
EAN code	8017709341824



Target

Potential users	Bars/Cafes; Restaurants/Catering
------------------------	-------------------------------------

Aesthetics

Series	Topline	Led colour	Green
Control Panel	Electronic		

Functions



Functions	5-stage filter; HTR; Door clearance 315mm
------------------	---

Programmes

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs; Cold water rinse program
Program options	Extra rinse; Clean water cycle
Program specifications	Boiler 71°C/Tank 60°C-60"; Boiler 71°C/Tank 60°C-1'20"; Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank 60°C-2'30"; Boiler 85°C / Tank 60°C - 1'; Boiler 71°C/Tank 60°C-1'10"; Boiler 85°C/Tank 60°C-4'10"
Drain and self cleaning cycle	Yes
Maximum baskets/hour	60
Maximum plates/hour	816

Maximum glasses/hour 960

Interface

Display	8 digit	Low detergent alert	Yes
Number of buttons	5	Cycle progress indicator	Yes
On/off indicator	Yes	End of cycle indicator	Yes
Low rinse aid alert	Yes	Manual diagnostics	Yes

Construction

Tank Construction	Deep drawn Double wall	Door gasket	On 3 sides
Tank material	Stainless steel AISI 304	Rack guides	Embossed
Back panel	Galvanized	Wash tank capacity	7 l
Door	Double skinned	Boiler capacity	4 l
Counter balanced door	Yes	Noise level	Lpa 56 dBA
Tank filter	Stainless steel	Protection class	IPX4
Wash arm	Stainless steel AISI 304	Adjustable feet	Yes
Rinse arm	Stainless steel AISI 304	Net weight (kg)	45,000 kg
		Drain max. height	600 mm

Technical Features

Tank heating element	1300 W	Warm water connection	8°C
Boiler heating element	2600 W	Inlet water maximum temperature	60°C
Wash pump	290 W	Max water hardness	12°f - 7°dH
Default connection	5200 W	Water inlet pressure	100-1000 kPa
Water consumption per cycle	2,3 l		

Electrical Connection

Plug	(G) UK e Singapore	Electrical connection options	230 V~ / 13 A / 2,9 kW / 50 Hz
------	--------------------	-------------------------------	--------------------------------


Equipment

Drain pump	Yes	Rinse aid flow rate	0.4 l/h
Peristaltic detergent pump	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse aid pump	Yes, electronic control	Break tank	Yes
Chemical level probe	Yes, optional KITSONLIV	Partial water exchange in the wash tank via built-in drain pump	Yes
Boiler thermostat	Yes	Water supply pipe diameter	DN10 - 3/8"
Soft Start	Yes	Drain supply pipe diameter	21.5 mm
Stand-by system	Yes		
Automatic start	Yes		

Detergent flow rate	1.5 l/h	Detergent (red) hose length	Yes, manual
		Rinse aid (blue) hose length	Yes, manual

Accessories Included

Glass basket	WB40G02	Water supply pipe	Yes - 1.5m
Flat basket	WB40G01	Drain pipe	Yes - 2m



R	PANNELLO RETRO LOWER BACK PANEL
Q	MORSETTO EQUIPOTENZIALE EARTH TERMINAL
P	TUBI POMPE PERISTALTICHE PERISTALTIC HOSES
E	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
S	TUBO DI SCARICO DRAIN HOSE
T	ENTRATA CAVO DI ALIMENTAZIONE DOSATORE ESTERNO EXTERNAL DISPENSER POWER CABLE ENTRY POINT
C	TUBO DI CARICO FILLER HOSE

Not included accessories



WB40D01

Wire basket for 8 dishes 400x400



PHOGR4

Glass basket for 400x400
glasswashers

Symbols glossary



HTR rinsing system



Max usable height 315mm



5 STAGE FILTER