

REFRIGERATOR ADVANCE K 70-4 C DR U

Product series: [Advance](#)

Item number: [131702030](#)

The Advance K 70-4 C DR U is a Refrigerator with a net internal volume of 415 liters. The outside dimensions are mm.

DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.



SPECIFICATIONS

Product title	Refrigerator	Energy consumption (kWh/Year)	548
Temperature Range	0/+10°C	Energy efficiency class standard	ISO 22041-2019
Volume, Gross (ltr.)	600	Energy efficiency class	C
Net Usable Volume (ltr.)	415	Energy Efficiency Index EEI	42.41
Exterior	Stainless	Sound Level – dB(A)	50
Interior	Stainless	Climate Class	5 (max. ambient 40°C w/ 40% RH)
Dimensions W x D x H (mm)	654 x 830 x 1975 (including castors)	Legs / Castors	H = 125 mm (C2)
Weight, Packed (kg)	122	Refrigerant (kg)	0.058
Insulation (mm)	60 (polyurethane)	CO2 equivalent (kg)	0.17
Refrigerant	R290	GN or Tray Size (mm)	2/1 GN deep
GWP	3	Maximum number of shelves	22, distance of 57 mm
Ref. capacity at -10°C (Watt)	361	Number of shelves	4
Power Supply	230V, 50 Hz	Equipped with	Right hand hinged reversible door with lock, automatic door closing, 4 grey shelves, LED lighting
Connection Load (Watt)	140	Door Type	Insulated Door