



- Insulated on all sides, including between each well
- Includes 6' (1.8 m) cord with plug. Does not require hardwiring
- Stainless steel control panel with individual controls
- Accepts full-size and fractional pans up to 6" (15.2 cm) deep
- Full-perimeter drip edge contains spills and condensation

## 1-Well Hot Drop-Ins

- Overall dimensions: 15" x 26" (38 x 66 cm)
- NEW: add "HD" to item number for marine-grade well



1000W STANDARD DRAIN	MANIFOLD WITH AUTOFILL	VOLTAGE	AMPS	PLUG	CONTROL
3646601	3646661	120	8.3	5-15P	Infinite
3646611	3646681	120	8.3	5-15P	Thermostatic
3646701	3646761	208-240	3.6 - 4.2	6-15P	Infinite
3646711	3646781	208-240	3.6 - 4.2	6-15P	Thermostatic

625W STANDARD DRAIN	MANIFOLD WITH AUTOFILL	VOLTAGE	AMPS	PLUG	CONTROL
36466	3646660	120	5.2	5-15P	Infinite
3646610	3646680	120	5.2	5-15P	Thermostatic
36467	3646760	208	3.0	6-15P	Infinite
3646710	3646780	208	3.0	6-15P	Thermostatic
36471	3647160	240	2.6	6-15P	Infinite
3647110	3647180	240	2.6	6-15P	Thermostatic

Note: Modular Drop-Ins cannot be canceled or returned  
 Note: HD wells have 2-year warranty

## 2-Well Hot Drop-Ins

- Overall dimensions: 28¼" x 26" (71.8 x 66 cm)
- NEW: add "HD" to item number for marine-grade well



1000W STANDARD DRAIN	MANIFOLD WITH AUTOFILL	VOLTAGE	AMPS	PLUG	CONTROL
3639901	3639961	120	16.7	5-30P	Infinite
3639911	3639981	120	16.7	5-30P	Thermostatic
3640001	3640061	208-240	7.2-8.3	6-15P	Infinite
3640011	3640081	208-240	7.2-8.3	6-15P	Thermostatic

625W STANDARD DRAIN	MANIFOLD WITH AUTOFILL	VOLTAGE	AMPS	PLUG	CONTROL
36399	3639960	120	10.4	5-15P	Infinite
3639910	3639980	120	10.4	5-15P	Thermostatic
36400	3640060	208	6.0	6-15P	Infinite
3640010	3640080	208	6.0	6-15P	Thermostatic
36472	3647260	240	5.2	6-15P	Infinite
3647210	3647280	240	5.2	6-15P	Thermostatic

Note: Modular Drop-Ins cannot be canceled or returned  
 Note: HD wells have 2-year warranty