

breite_
0.pdf



MRFvd 3511

Performance

LED

Gross capacity	347 litre
Ext. dimensions in mm (w/d/h)	597/654/1684
Int. dimensions in mm (w/d/h)	475/423/1459
Energy efficiency class	
Energy consumption in 365 days	531.86 kWh
Climate rating/Temperature class	CC2 / K4
Ambient temperature range	+10°C to +40°C ¹
Refrigerant	R 600a
Noise output	50 dB(A)
Connection Rating	2.0 A
Frequency/voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Housing material/colour	steel/grey
Door material	Insulated glazed door
Liner Material	moulded polystyrol white
Type of Control	analogue controls
Temperature display	external digital
Interior light	LED
Adjustable Shelving	4
Loading capacity 0.5L PET/facings 0.5L PET	207/7
Loading capacity 0.33L can/facings 0.33L can	414/7
Shelf loading	45 kg
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	50/45 mm
Gross/net weight	78/72 kg
EAN-Nr.	9005382232477

¹ Indicates the ambient temperature at which the device can be operated safely.