Breville Commercial



Consistent, repeatable results

The HydroPro™ Plus initiates a new generation of professional sous vide immersion circulators. Featuring Sous Vide Toolbox™, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The HydroPro™ Plus includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the HACCP Manager App via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to 'My Presets' and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

Visit www.brevillecommercial.com to learn about the entire line of Breville | Commercial products and great recipe ideas.

Sous Vide Immersion Circulator

Technical Specifications

PERFORMANCE

Power	1450 Watts
Flow Rate	17 L/Min
Max Water Bath Size	45L with lid
DURABILITY	
• IPX7 Water Resistant	Stainless Steel Exterior

- · NSF and cUL Commercially Certified









- Stainless Steel Exterior
- · Ruby Bearing
- Tungsten Carbide Shaft

PRECISION

Temperature Resolution	0.1°F/0.1°C
Temperature Stability	± 0.1°F/0.1°C
Maximum Water Temperature	194°F/90°C
IISARII ITV	

Color TFT Touch Display	
On-board Cooking Guide Sous Vide Toolbox™	
Manual Time & Temperature Controls	
Integrated Digital Probe	
Variable Flow Speed	
-	

360° Adjustable Flow Direction Coil-less Heating Chamber Low Water Detection Magnetic Impeller Coupling Adjustable & Detachable Clamp

Carry Case with Handle.

CONNECTIVITY

Bluetooth

WEIGHTS & DIMENSIONS	
Unit Weight	4.2lb / 2kg
Unit Dimensions (L x D x H)	3.7in x 6.7in x 14.6in / 9.4cm x 17.0cm x 37.0cm
Shipping Weight	27.6lb / 12.5kg
Shipping Dimensions (L x D x H)	9.6in x 26.6in x 17.4in / 24.3cm x 67.5cm x 44.2cm
SKU Number	CSV750PSS1BUC1
ACCESSORIES	Adjustable & Detachable Clamp
	Magnetic Impeller
	360° Adjustable Flow Direction Foot
	Digital Probe & Calibration Holder