




SLICER CCE-350 230/50/1

Blade Ø 350mm.



P/N 5050072



SPECIFICATIONS

Blade diameter: 350 mm

Cutting capacity

- ✓ Square cut: 250 mm x 250 mm
- ✓ Round cut: 250 mm
- ✓ Rectangular cut: 250 mm x 320 mm

Slice thickness: 0 mm - 18 mm

Carriage run: 375 mm

Total loading: 430 W

IP Protection grade: 43

Electrical supply: 230 V / 50 Hz / 1 ~

Plug: EU

External dimensions (WxDxH)

✓ Width: 780 mm

✓ Depth: 800 mm

✓ Height: 580 mm

Net weight: 43 Kg

Crated dimensions

840 x 780 x 730 mm

Gross weight: 63 Kg.

SALES DESCRIPTION

Vertical position for universal application. Specially suitable for fresh meat.

- ✓ Slicer Fully made of high-polished anodised aluminium.
- ✓ Professional slicer with ring, carriage lock and blade removal tool.
- ✓ Built-in precision sharpener. Hard-chromed forged scoop knife.
- ✓ Life-lubricated helicoidal gear drive.
- ✓ Easy selection of cutting thickness from 0 to 25 mm.
- ✓ Advancement of the product on double carriage
- ✓ Bearing-mounted slide plate.
- ✓ Components in contact with food are completely detachable for easier cleaning.



www.sammic.co.uk

Food Service Equipment Manufacturer
 Unit 2, Trevanah Road
 Troon Industrial Park
 LE4 9LS - Leicester
uksales@sammic.com
 Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

DYNAMIC PREPARATION
GEAR DRIVEN SLICERS

product sheet
updated 30/07/2018