



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
 CUN-22G C CI 230V 1N 50Hz

19090900

23/01/2024

DENOMINATION:

Freezer cabinet - Concept Gastronorm with 2 compartments and 2 door, at 50Hz.

DESCRIPTION :

- Structure built with AISI-304 stainless steel.
 - 60 mm, 40 kg/m³ injected polyurethane insulation.
 - Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
 - Forced draught cooling system with hermetically sealed compressor.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class 4..
 - Inner LED lights with power switch (in refrigerated cabinets and now also in freezing units).
- Freezer cabinet
 Visibility: vertical LED light for greater visibility.

POSSIBLE OPTIONS :

- Stainless Backing
- Legs instead of castors
- Locks
- Pedal

STANDARD OPTIONS :

- Door frame resistance
- Castors
- UK plug

POSSIBLE ACCESSORIES :


- REFRIGERATION
- ACCESSORIES
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12037958 GN-2/1 GRID made in Epoxi (650x530) 6

DIMENSIONS

X Width	1318 mm	X Gross width	1460 mm
Y Depth	842 mm	Y Gross depth	880 mm
Z Height	2040 mm	Z Gross height	2063 mm
Net Weight	227,0 kg	Gross Weight	240,0 kg
Net volume	2,264 m ³	Gross volume	2,596 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	4,4 A
Electric frequency	50Hz
Electric power	0,749 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-290
----------	-------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	4793,00 kWh
Clasif. Energy efficiency	E
Climate class	4
Cooling gas load	138,000 g
Energy Efficiency Index	83,81 %
Frozen net.vol	874 L
Gross internal volume	1186 L
Model Type	Vertical cabinet
Power consumption 24h	13,27 kWh
Refrigeration power	0,907 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-4A
--------------------------	----------

OTHERS

Condensation system	Vent.
---------------------	-------







Catalogue
FOOD SERVICE
Chapter
REFRIGERATION


Specific model
CUN-22G C CI 230V 1N 50Hz

19090900





23/01/2024




SECTION B-B




SECTION A-A




E
ELECT.



"R" OPTION



C
132 < X < 192



D
"PD" OPTION