

SPG505UK

Product Family	Dishwasher
Subfamily	Undercounter glasswashers
Line	Ecoline
Basket dimensions	500x500 mm
Rinse pump	HTR system
Wash pump	Standard
Default power supply	230 V~ / 30 A / 6,8 kW / 50 Hz



Accessories Included

Flat basket	2x PB50G02	Drain pipe	Yes - 2m
Water supply pipe	Yes - 1.5m		

Target

Potential users	Bars/Cafes
-----------------	------------

Programmes

Maximum baskets/hour	40
Maximum plates/hour	720

Interface

Display	4 digit	On/off indicator	Yes
Number of buttons	5	Manual diagnostics	Yes

Construction

Tank	Deep drawn	Hood elevation system	Manual
Construction	Partial double wall	Filter	4-stages filter system
Tank material	Stainless steel AISI 304	Wash tank capacity	13 l
Back panel	Galvanized	Boiler capacity	6 l
		Noise level	Lpa 55.5 dBA

Upper washing system	One washing and one split rinse spray arms, stainless steel	Protection class	IPX4
Lower washing system	One washing and one combined rinse spray arms, stainless steel and plastic	Adjustable feet	Yes
Tank filter	Plastic	Drain max. height	600 mm
Door gasket	Top only		
Rack guides	Embossed		

Technical Features


Trays washing option	Yes	Water inlet pressure	1-6 bar / 100-600 kPa
Water consumption per cycle	3,2 l	Detergent flow rate	1.5 l/h
Wash temperature (min-max)	60 °C	Rinse aid flow rate	0.4 l/h
Rinse temperature (min-max)	85 °C	Usable load height	365 mm
Warm water connection	8°C	Depth with door open	1000 mm
Max. inlet temperature	60°C	Dimensions	578x600x814 mm
Max water hardness	12°f - 7°dH		

Electrical Connection

Tank heating element power	2000 W	Default connection	6800 W
Boiler heating element power	6100 W	Electrical connection options	230 V~ / 12 A / 2,7 kW / 50 Hz; 230 V~ / 15 A / 3,4 kW / 50 Hz ; 230 V~ / 20 A / 4,5 kW / 50 Hz ; 400 V 3N~ / 12 A / 6,8 kW / 50 Hz
Wash pump power	700 W		

Equipment

Drain pump	Yes	Option for auto daily switch on	Yes
Peristaltic detergent dispenser	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	Break tank	Yes
Chemical dosing	gr/lit	Partial water exchange in the wash tank via built-in drain pump	Yes
Rinse boiler Thermostop system	Yes - default	Water supply pipe diameter	16 mm
Wash tank Thermostop system	Yes	Drain supply pipe diameter	21.5 mm
Wash pump soft start system	Yes	Detergent (red) hose length	Yes, manual
Stand-by system	Yes	Rinse aid (blue) hose length	Yes, manual




R	Pannello retro	Lower back panel
Q	Morsetto equipotenziale	Earth terminal
C	Tubo di carico	Filler hose
S	Tubo di scarico	Drain hose
P	Tubi pompe peristaltiche	Peristaltic hoses
E	Cavo alimentazione elettrica	Electricity supply cable

Compatible Accessories



KITSONLIV
Probe level kit




PB50G02
Universal basket in polypropylene
500x500



PHOOS02
Basket in polypropylene for cutlery with
6 compartments



WH00S01
Wire insert for 12 small dishes



PB50D01
Basket made of polypylene for 18
plates 500x500



PHOOS01
Single basket in polypropylene for
cutlery



WB50PG5
Wire basket with flat bottom for 25
plastic glasses, dim. (WxDxH)
500x500x260 mm



WS5
Underframe for glasswashers 500mm

Symbols glossary



Suitable for 1/1GN trays



HTR rinsing system



5 stand filter



MAX.USABLE HEIGHT 365mm

Benefit

Hood lift

Unprecedented comfort with the patented lifting system

The new ergonomic handle, combined with the patented lifting system, minimises the effort required to open and close the hood, limiting it to just 2.5 kg. This system ensures an exceptionally smooth and lightweight operation, helping to protect the operator's health and well-being, even during extended use.

HTR System

Consistent temperatures and pressures for uniform and effective dishwashing

Thanks to the HTR system (High Temperature Rinse) and the presence of the atmospheric boiler combined with the Thermostop, the cold inlet water does not enter the boiler during rinsing, ensuring a constant temperature of 85°C. The HTR system keeps the water hot for deep sanitisation and quick drying, ensuring constant pressure for uniform and effective cleaning.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

4-stage filtration system

Deep cleaning and spotless washes with the Patented 4-Stages Filtration System

The innovative Smeg filtration system consists of 4 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd stages, finer particles are captured at this filtration stage; the 3th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

Partial double skin

Optimised thermal and acoustic insulation

The double-skin design of the Ecoline features dual insulation on the door, top, and rear panel, while the side panels have a single layer of insulation. This structure optimises energy efficiency by minimising heat loss. Additionally, it provides effective acoustic insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Interface

Control panel with electronic buttons

The electronic control panel features an intuitive interface with soft-touch buttons, allowing easy selection of one of the three wash programmes: short, medium, or intensive. There are also buttons for power, selection, and cycle start. The display provides real-time monitoring of the tank and boiler temperature, as well as diagnostics, ensuring effortless and immediate control of the main functions.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.