

C65WSD 2.7kW 13Amp



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



↗	Overall dimensions (W x D x H)	<i>mm</i>	575 x 700 x 850
	Packaging dimensions (W x D x H)	<i>mm</i>	670 x 780 x 1000
	Gross weight	<i>Kg</i>	66
	Net weight	<i>Kg</i>	61
	Cubic volume	<i>m³</i>	0.52
☐	Rack size	<i>mm</i>	500 x 600
	Door opening	<i>mm</i>	405
	Max useable height	<i>mm</i>	380
	Rack guide rails		embossed
	Body construction		stratified double skin
🔥	Tank construction		welded - stamped base
	Tank volume	<i>L</i>	23
	Tank heating element	<i>kW</i>	2.0
	Surface scrap trays		composite (2mm mesh)
	Wash arms		parallel Y (quick release)
🌡️	Wash pump type		dual flow
	Wash pump power	<i>kW</i>	0.7
	Wash temperature	<i>°C</i>	55 - 60 (adjustable)
🔥	Boiler type		open
	Boiler volume	<i>L</i>	6.0
	Breaktank		yes
🌡️	Boiler heating element	<i>kW</i>	2.0
	Rinse booster pump		yes
	Rinse booster pump power	<i>kW</i>	0.15
	Rinse temperature	<i>°C</i>	70 - 85 (adjustable)
🌡️	Rinse arms		parallel Y (quick release)
	Drain system		partial drain
	Drain filter		triple filter
📉	Drain pump		yes
	Rinse aid dispenser	<i>peristaltic</i>	yes
	Detergent dispenser	<i>peristaltic</i>	yes
🍷	Water consumption per cycle	<i>L</i>	1.8 - 2.6
	Inlet water pressure	<i>bar</i>	0.5 - 6.0
	Fast program (GLS1)	<i>sec</i>	80
⚡	Total programs	<i>programs</i>	9
	Total power	<i>kW</i>	2.7
	Electric connection	<i>V-Ph-Hz</i>	230-240V 1N 50Hz
🔌	<i>Alternative</i>		not convertible
	Fuse	<i>A</i>	13 (moulded plug)
	Water softener		yes (continuous)



Supplied with

Flat rack	1
Plate rack	1
Cutlery rack	1
Electric cable	1
Drain hose	1
Fill hose	1

C65WSD 7.7kW 16Amp 3 Phase



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



C65WSD

	Overall dimensions (W x D x H)	mm	575 x 700 x 850
	Packaging dimensions (W x D x H)	mm	670 x 780 x 1000
↙	Gross weight	Kg	66
	Net weight	Kg	61
	Cubic volume	m ³	0.52
	Rack size	mm	500 x 600
☐	Door opening	mm	405
	Max useable height	mm	380
	Rack guide rails		embossed
	Body construction		stratified double skin
	Tank construction		welded - stamped base
🔥	Tank volume	L	23
	Tank heating element	kW	2.0
	Surface scrap trays		composite (2mm mesh)
TANK 🌡️	Wash arms		parallel Y (quick release)
	Wash pump type		dual flow
	Wash pump power	kW	0.7
	Wash temperature	°C	55 - 60 (adjustable)
🔥	Boiler type		open
	Boiler volume	L	6.0
	Breaktank		yes
	Boiler heating element	kW	5.0
BOILER 🌡️	Rinse booster pump		yes
	Rinse booster pump power	kW	0.15
	Rinse temperature	°C	70 - 85 (adjustable)
	Rinse arms		parallel Y (quick release)
🚰	Drain system		partial drain
	Drain filter		triple filter
	Drain pump		yes
💧	Rinse aid dispenser	peristaltic	yes
	Detergent dispenser	peristaltic	yes
	Water consumption per cycle	L	1.8 - 2.6
🍷	Inlet water pressure	bar	0.5 - 6.0
	Fast program (GLS1)	sec	80
	Total programs	programs	9
⚡	Total power	kW	7.7
	Electric connection	V-Ph-Hz	400V 3+N 50Hz
	Fuse	A	16
🔌	Water softener		yes (continuous)



Supplied with

Flat rack	1
Plate rack	1
Cutlery rack	1
Electric cable	1
Drain hose	1
Fill hose	1

C65WSD 6.7kW 30Amp



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



↗	Overall dimensions (W x D x H)	mm	575 x 700 x 850
	Packaging dimensions (W x D x H)	mm	670 x 780 x 1000
	Gross weight	Kg	66
	Net weight	Kg	61
☒	Cubic volume	m ³	0.52
	Rack size	mm	500 x 600
	Door opening	mm	405
	Max useable height	mm	380
	Rack guide rails		embossed
	Body construction		stratified double skin
	Tank construction		welded - stamped base
🔧	Tank volume	L	23
	Tank heating element	kW	2.0
🌡️	Surface scrap trays		composite (2mm mesh)
	Wash arms		parallel Y (quick release)
	Wash pump type		dual flow
	Wash pump power	kW	0.7
	Wash temperature	°C	55 - 60 (adjustable)
	Boiler type		open
🕒	Boiler volume	L	6.0
	Breaktank		yes
🌡️	Boiler heating element	kW	6.0
	Rinse booster pump		yes
	Rinse booster pump power	kW	0.15
	Rinse temperature	°C	70 - 85 (adjustable)
🚰	Rinse arms		parallel Y (quick release)
	Drain system		partial drain
	Drain filter		triple filter
💧	Drain pump		yes
	Rinse aid dispenser	peristaltic	yes
🍷	Detergent dispenser	peristaltic	yes
	Water consumption per cycle	L	1.8 - 2.6
	Inlet water pressure	bar	0.5 - 6.0
⚡	Fast program (GLS1)	sec	80
	Total programs	programs	9
	Total power	kW	6.7
	Electric connection	V-Ph-Hz	230-240V 1N 50Hz
⚡	Alternative		230-240V 1N 2.7kW 13A*
	Alternative		230-240V 1N 4.7kW 20A
	Fuse	A	30
🔗	Water softener		yes (continuous)



Supplied with


Flat rack	1
Plate rack	1
Cutlery rack	1
Electric cable	1
Drain hose	1
Fill hose	1

*Moulded plug

C65WSD



Buttress Group Ltd.
Top Station Road, Brackley,
Northants NN13 7UG, UK



All services must be within 1 metre