

PROJECT:		
ITEM#_	(QTY:
MODEL#		
AIA #	SIS #	

SANDWICH PREP REFRIGERATOR WITH DRAWERS

VSPD36HC-10-2



EXCLUSIVE WARRANTY

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)











CABINET CONSTRUCTION

- Stainless Steel Exterior (galvanized back and bottom)
- · Aluminum Interior
- · Hinged, Insulated Flat Lift-Up Lid
- · One-Piece, Snap-In Magnetic Drawer Gaskets
- · Heavy-Duty Aluminum Pan Liner
- · 8' Cord And Plug (see electrical data for details)

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Rear Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- **Epoxy Coated Evaporator Coil**
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F

FEATURES

- Full Electronic Control
- Low Profile Horizontal Drawers Handles
- Stay-Open Drawer Feature For Easy Product Loading
- Top Accommodates Up To 6" Deep Food Service Pans With Locking Divider Bars
- Heavy-Duty Stainless Steel Drawer Frames
- Telescoping Drawers Slides With Locking Mechanism
- Accommodates 6" Deep Food Service Pans In Both Upper And Lower Drawers (pans not included)
- 10" Cutting Board Constructed Of White Polyethylene **Plastic**
- 6" Casters Two With Brakes



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- · Stainless Steel Interior
- · Stainless Steel Back
- · Drawer Locks
- 18 Pan Cover
- Garnish Rack (full & half pan)
- · 12" Cross Bar
- · Front Or Side Crumb Catcher
- · Roll Top Cover
- · 6" Legs Or 6" Seismic Legs
- · Casters: 3", Roller Kit, Low Profile
- · Correctional Package
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 fax: (800) 253-5168


Rev. 7/1/24 Printed in U.S.A. APPROVAL: __ DATE: _





VSPD36HC-10-2











We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

2" Bottom & 2" Rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	10.0	Cabinet Voltage	115/60/1	Height	49"	
Width, Overall (in.)	36"	Total Amperes	2.2	Width	38"	
Depth, Overall (with handle)	32 3/4"	NEMA Plug (8' cord)	5-15P	Depth	32"	
Height Overall (6" casters)	51"	REFRIGERATION DATA		Crated Weight	326 lbs	
Depth, Drawer Extended	48 3/4"	Condensing Unit Size, HP	1/6	*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at		
Drawer Openings (in.)	31 3/4" x 7 5/8" 31 3/4" x 11 3/8"	Refrigerant*	R-290			
No. Of Drawers	2	Capacity (BTU/HR) (100°F/20°F)	1094			
No. Of Pans	10	Heat Rejection (BTU/HR)	1641	time of order.		
		Charge (lbs/grams/ounces)	0.243 / 110 / 3.89			

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 7/1/24 Printed in U.S.A.

