

{15.01}

Super Erecta® Hot Shelving



Shelves that keep food hot, appetizing, and ready-to-go.

Flexible Design: Configure heated holding solutions almost anyway imaginable by combining with other Super Erecta® shelving systems to create

- Stand alone heated holding solutions
- Storage solutions with integrated heated holding
- Workstations with integrated heated holding

Consistent Heat Distribution: High quality, Type 304 stainless steel construction combined with aluminum inner core for consistent, reliable radiant heat across each shelf. Adjustable thermostat, 200°F (93°C) maximum surface temperature.

Low Wattage Design: Requires less power to operate and lower energy consumption.

Adjustability: Shelves can be adjusted at 1" (25mm) increments to customize to desired shelf spacing. Compatible with all Super Erecta SiteSelect posts

Cleanable and Durable: Smooth corrosion resistant stainless steel surfaces are easy-to-clean and durable to stand up to daily usage.

Shelf Sizes: 18 different shelf sizes to choose from.

- 3 depths: 14" (356mm), 18" (457mm), 24" (610mm),
- 6 lengths: 24" (610mm), 30" (762mm), 36" (914mm), 42" (1067mm), 48" (1219mm), 60" (1524mm).

Plastic feet included with every shelf. Posts ordered separately.

Enclosed Shelf Kits: Extend holding time with pass-thru enclosure kits that include a heated shelf, non-heated stainless shelf, side panels, hinged doors on control side, and sliding doors on opposite side.
9 sizes to choose from.

- 3 depths 14" (356mm), 18" (457mm), 24" (610mm)
- 3 lengths 36" (914mm), 42" (1067mm), 48" (1219mm).

Posts ordered separately.

Easy Order Workstations: 5 pre-configured assembly / prep stations with integrated heated holding to boost operational efficiency. 3 models with an open heated shelf and 2 models with an enclosed heated shelf.

Warranty: 2 year parts & labor warranty



Shown as a stand alone counter-top unit with plastic feet.



Shown as a tiered shelving unit.



Shown with heated shelf, enclosure kit and standard Super Erecta shelving.



Heated shelf enclosure kit shown with a Super Erecta workstation.



All Metro Catalog Sheets are available on our website: metro.com

Specifications

Construction: Type 304 stainless steel exterior surfaces with black epoxy coated corners. Each shelf includes (4) polymer split sleeves to mount to Super Erecta SiteSelect posts (posts sold separately). (4) 3" polymer feet to use on countertop as a heated worksurface.

Heating System: Thermostatically controlled, low wattage foil elements adhered to aluminum diffuser to evenly heat the stainless steel surface with hot air. On / Off power switch and thermostat provide separate individual control of every shelf.

Power Cord: Each shelf has a permanently mounted 6' (183cm) long cord with NEMA 5-15P plug end.

Clearance Requirements: Minimum clearance from bottom of shelf to combustible surface is 1.5" (38mm). Recommended minimum spacing between shelves is 5.73" (146mm)

Shelves

Includes shelf, one bag of split sleeves and (4) plastic feet (posts not included). For actual dimensions add 5/8" (16mm) to depth and subtract 1/16" (2mm) from length.




Use with Super Erecta Posts or Countertop Feet



Depth x Length		120V, 60Hz Models		220-240V, 50/60Hz Models			
(in.)	(mm)	NEMA-515P Plug Model No.	Electrical Specifications	CEE 7/7 Schuko Plug Model No.	BS-1363 Plug Model No.	Electrical Specifications	Approx. Shipping Weight
14x24	356x610	HS1424	200W, 1.7A	HSX1424-EU	HSX1424-UK	168-200W, 0.76-0.83A	14.5 lbs (6.6 kg)
14x30	356x762	HS1430	200W, 1.7A	HSX1430-EU	HSX1430-UK	168-200W, 0.76-0.83A	17.2 lbs (7.8 kg)
14x36	356x914	HS1436	400W, 3.4A	HSX1436-EU	HSX1436-UK	336-400W, 1.53-1.67A	20.3 lbs (9.2 kg)
14x42	356x1067	HS1442	400W, 3.4A	HSX1442-EU	HSX1442-UK	336-400W, 1.53-1.67A	23.1 lbs (10.5 kg)
14x48	356x1219	HS1448	400W, 3.4A	HSX1448-EU	HSX1448-UK	336-400W, 1.53-1.67A	25.8 lbs (11.7 kg)
14x60	356x1524	HS1460	600W, 5.0A	HSX1460-EU	HSX1460-UK	504-600W, 2.29-2.50A	31.7 lbs (14.4 kg)
18x24	457x610	HS1824	200W, 1.7A	HSX1824-EU	HSX1824-UK	168-200W, 0.76-0.83A	17.5 lbs (8.0 kg)
18x30	457x762	HS1830	200W, 1.7A	HSX1830-EU	HSX1830-UK	168-200W, 0.76-0.83A	21.0 lbs (9.5 kg)
18x36	457x914	HS1836	400W, 3.4A	HSX1836-EU	HSX1836-UK	336-400W, 1.53-1.67A	24.8 lbs (11.3 kg)
18x42	457x1067	HS1842	400W, 3.4A	HSX1842-EU	HSX1842-UK	336-400W, 1.53-1.67A	28.3 lbs (12.8 kg)
18x48	457x1219	HS1848	400W, 3.4A	HSX1848-EU	HSX1848-UK	336-400W, 1.53-1.67A	31.8 lbs (14.4 kg)
18x60	457x1524	HS1860	600W, 5.0A	HSX1860-EU	HSX1860-UK	504-600W, 2.29-2.50A	38.0 lbs (17.7 kg)
24x24	610x610	HS2424	200W, 1.7A	HSX2424-EU	HSX2424-UK	168-200W, 0.76-0.83A	22.1 lbs (10.0 kg)
24x30	610x762	HS2430	400W, 3.4A	HSX2430-EU	HSX2430-UK	336-400W, 1.53-1.67A	27.0 lbs (12.3 kg)
24x36	610x914	HS2436	400W, 3.4A	HSX2436-EU	HSX2436-UK	336-400W, 1.53-1.67A	31.6 lbs (14.3 kg)
24x42	610x1067	HS2442	600W, 5.0A	HSX2442-EU	HSX2442-UK	504-600W, 2.29-2.50A	36.4 lbs (16.5 kg)
24x48	610x1219	HS2448	600W, 5.0A	HSX2448-EU	HSX2448-UK	504-600W, 2.29-2.50A	41.0 lbs (18.6 kg)
24x60	610x1524	HS2460	800W, 6.7A	HSX2460-EU	HSX2460-UK	672-800W, 3.06-3.33A	49.9 lbs (22.6 kg)

Enclosed Shelf Kits

Includes heated shelf, non-heated stainless shelf, side panels, hinged doors on control side, sliding doors on opposite side, and split sleeves for each shelf (posts not included).



Unit shown with enclosure kit installed. Posts & additional shelves must be ordered separately.

Dimensions Length x Depth x Height		120V, 60Hz Models		220-240V, 50/60Hz Models			Approx. Shipping Weight
(in.)	(mm)	NEMA-515P Plug Model No.	Electrical Specifications	CEE 7/7 Schuko Plug Model No.	BS-1363 Plug Model No.	Electrical Specifications	
36.7x17.7x17.4	933x450x442	HS1436-EKIT	400W, 3.4A	HSX1436-EKIT-EU	HSX1436-EKIT-UK	336-400W, 1.53-1.67A	71.3 lbs (32.3 kg)
42.7x17.7x17.4	1085x450x442	HS1442-EKIT	400W, 3.4A	HSX1442-EKIT-EU	HSX1442-EKIT-UK	336-400W, 1.53-1.67A	79.7 lbs (36.2 kg)
48.7x17.7x17.4	1237x450x442	HS1448-EKIT	400W, 3.4A	HSX1448-EKIT-EU	HSX1448-EKIT-UK	336-400W, 1.53-1.67A	86.7 lbs (39.3 kg)
36.7x 21.7x17.4	933x552x442	HS1836-EKIT	400W, 3.4A	HSX1836-EKIT-EU	HSX1836-EKIT-UK	336-400W, 1.53-1.67A	78.3 lbs (35.5 kg)
42.7x 21.7x17.4	1085x552x442	HS1842-EKIT	400W, 3.4A	HSX1842-EKIT-EU	HSX1842-EKIT-UK	336-400W, 1.53-1.67A	86.5 lbs (39.2 kg)
48.7x21.7 x17.4	1237x552x442	HS1848-EKIT	400W, 3.4A	HSX1848-EKIT-EU	HSX1848-EKIT-UK	336-400W, 1.53-1.67A	94.7 lbs (42.9 kg)
36.7x27.7 x17.4	933x704x442	HS2436-EKIT	400W, 3.4A	HSX2436-EKIT-EU	HSX2436-EKIT-UK	336-400W, 1.53-1.67A	89.3 lbs (40.5 kg)
42.7x 27.7x17.4	1085x704x442	HS2442-EKIT	600W, 5.0A	HSX2442-EKIT-EU	HSX2442-EKIT-UK	504-600W, 2.29- 2.50A	98.3 lbs (44.6 kg)
48.7x 27.7x17.4	1237x704x442	HS2448-EKIT	600W, 5.0A	HSX2448-EKIT-EU	HSX2448-EKIT-UK	504-600W, 2.29- 2.50A	106.6 lbs (48.3 kg)

Workstations with Open Heated Over Shelf

Includes 24" deep stainless steel worksurface, 3 sided open frame to allow under counter storage, stationary posts, and 14" deep overhead heated & wire shelves.



NEMA 5-15P Plug 120V Model No. & Electrical Specifications	Nominal Length x Depth x Height (in.) (mm)	Approx. Shipping Weight	Approx. Shipping Volume
EZHS36W-KIT 120V, 400W, 3.4A 36x24x64	914x610x1613	78.0 lbs (35.4 kg)	7.0 ft³ (0.20 m³)
EZHS48W-KIT 120V, 400W, 3.4A 48x24x64	1217x610x1613	93.6 lbs (42.4 kg)	8.9 ft³ (0.25 m³)
EZHS60W-KIT 120V, 600W, 5.0A 60x24x64	1522x610x1613	109.2 lbs (49.5 kg)	10.9 ft³ (0.31 m³)

Note: Not available in 220-240V.



Workstations with Enclosed Heated Over Shelf

Includes 24" deep stainless steel worksurface, 3 sided open frame to allow under counter storage, stationary posts, and 14" deep overhead enclosed heated shelf.



NEMA 5-15P Plug 120V Model No. & Electrical Specifications	Nominal Length x Depth x Height (in.) (mm)	Approx. Shipping Weight	Approx. Shipping Volume
EZHSE36W-KIT 120V, 400W, 3.4A 36x24x64	914x610x1613	120.0 lbs (54.4 kg)	10.5 ft³ (0.30 m³)
EZHSE48W-KIT 120V, 400W, 3.4A 48x24x64	1217x610x1613	142.9 lbs (64.8 kg)	13.4 ft³ (0.38 m³)

Note: Not available in 220-240V.



{15.01}



Super Erecta® Hot Shelving

Replacement Parts & Accessories

Replacement Split Sleeves: **Model # 9985**
(bag of 4 sets)



Replacement Feet: **Model # 3FHS-4PK**
(Qty = 4)



Plastic Post Glides: **Model # 9991P**
(Qty = 1)
For use in countertop applications.



Thermostat Cover: **Model # HS-THERMCOVER**



4 Outlet Power Strip: **Model # HS-PSTRIP4**
(120V, 15A, 1800W)



SiteSelect™ Posts

Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification. Stationary post heights include leveling foot, mobile posts for use with stem casters.



Stationary Post

Post for Stem Caster

Stationary Posts

Model. No. Chrome	Model. No. Stainless Steel	Actual Height		Approx Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
7P	-	7.375	187	0.5	0.3
13P	13PS	14.375	365	1	0.5
27P	27PS	28.375	720	1.75	0.75
33P	33PS	34.375	873	2	0.9
54P	54PS	54.4375	1382	3	1.4
63P	63PS	62.4375	1585	3.5	1.6
74P	74PS	74.5	1892	4	1.8
86P	86PS	86.5	2197	5	2.3
*96P	-	96.5	2450	5.5	2.5

Mobile Posts

Model. No. Chrome	Model. No. Stainless Steel	Actual Height		Approx. Pkd. Wt.	
		(in.)	(mm)	(lbs.)	(kg)
13UP	13UPS	13.75	349	1	0.5
27UP	27UPS	27.75	704	1.75	0.75
33UP	33UPS	33.75	857	2	0.9
54UP	54UPS	53.8125	1366	3	1.4
63UP	63UPS	61.8125	1570	3.5	1.6
-	-	69.75	1771	3.75	1.7
74UP	74UPS	73.875	1876	4	1.8
86UP	86UPS	85.875	2181	4.5	2.0