



in association with



Inspired by Scandinavia

## WMC6763 Washing Machine



Kg Load



Steel Seal™



Active Drum™



G-Factor

Shortest cycle time



Super Quick Wash 60°C



WiFi for ConnectLife



Prepared connection to external auto dosing units



Prepared connection to external payment systems



## Quick Overview

- Maximum spin speed: 1600 rpm
- Finish: Touch Proof™ Stainless steel
- 26 programmes
- Connection: 230V / 1ph / 16A / 50Hz / 3kW
- Electrical reconfiguration: Yes, 400V / 3ph / 10A / 3kW or 230V / 1ph / 10A / 2kW
- Pump and valve drain system machines available
- Prepared for Auto Dosing: Yes
- WiFi for ConnectLife: Yes
- Prepared for payment systems (coin, card and AIRwallet): Yes

### Construction

**Operating position:** Front-operated

**Capacity:** 7kg

**Door opening:** 31cm

**Door opening angle:** 180°

**Door opening:** Left hinge

**Material:** Stainless steel

**Base plate:** Waterproof with flood sensor

**Drum volume:** 60L

### Electrics

**Connection power:** 3,200W

**Fuse:** 16A

**Electrical connection:** 220-240V

**Frequency:** 50Hz

**Length of power cable:** 2.1m

**Phases:** 1

### Connection of water/drain

**Cold and hot water connection:** Size 3/4" (adapter 1/2" included)

**Inlet hose:** PEX inlet hose, able to withstand 10 bar at 95°C (tested to over 50 years)

**Drainage capacity:** 20l/min

**Drain system:** Drain valve or pump available

### Dimensions

**Dimensions (H x W x D):** 850 x 595 x 591mm

**Packaging dimensions:** 920 x 640 x 661mm

**Net weight:** 76.5kg

**Gross weight:** 79.7kg

**Adjustable feet:** 10mm

**Depth with door open:** 965mm

**Inlet hose, length:** 1,500mm

**Inlet hose:** 1,600mm

# WMC6763 Washing Machine



Drain pump version shown



Functions
<b>Spin setting:</b> Fixed
<b>Detection and automatic correction of imbalance in the drum:</b> Yes
<b>Flood protection:</b> Yes
<b>Delayed start:</b> Yes, up to 100 hours
<b>Possible to connect and control via WIFI:</b> Yes
<b>Overheating protection:</b> For motor and electronics

Performance
<b>Residual humidity:</b> 44%
<b>Heater power:</b> 3,000W
<b>Temperature range:</b> Cold - 90°C

Operations
<b>Display type:</b> LCD display
<b>Language:</b> CN, HR, CZ, DK, NL, EN, EE, FI, FR, DE, IT, JP, LV, LT, NO, PL, RU, SK, SL, ES, SE
<b>Detergent dispenser:</b> Three compartment dispenser

Programmes		
Allergy cotton 60°C	White/Coloured wash 60°C Professional	Wool and hand wash 40°C
Allergy cotton 90°C	White/Coloured wash 40°C Professional	MOP wash 60°C
Allergy synthetics 60°C	Quick 60°C Professional	MOP wash 90°C
Drum cleaning	Quick 40°C Professional	Microfibre 40°C
Allergy synthetics 40°C	White/colour 20 °C	Microfiber wash 60°C
Eco 40-60 °C	Synthetic wash 40°C Professional	Disinfection 60°C
Rough wash 90°C	Drain	Disinfection 40°C
Rough wash 60°C	Spin	Disinfection 90°C
White wash 90°C Professional	Rinse	

## DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: 01749 870055 e: sales@dcproducts.co.uk w: www.laundry.dcproducts.co.uk