
C SERIES

2-SECTION COMPACT 4-DRAWER UNDERCOUNTER REFRIGERATOR

Project Name:	Location:		AIA #:
Item #:	Qty:	Model #:	SIS #:

C SERIES - STAINLESS STEEL EXTERIOR & INTERIOR




60” WIDE MODEL


CLUC-60R-DW (Drawers left and right sections)
CLUC-60R-DW-LD (Drawers on right side; Left hinged door left side)
CLUC-60R-DW-DR (Drawers on left side; Right hinged door right side)

ENERGY STAR® Listed Commercial Refrigerator
For full listing visit energystar.gov


PLAN VIEW



ELEVATION



SIDE VIEW



SINGLE DRAWER
PAN LAYOUT

SPECIFICATIONS

DIMENSIONAL DATA	
Pan Capacity (per drawer)	(1) Full Size
Length in.	60-1/4 (153 cm)
Depth in.	31-1/2 (80 cm)
Overall Height in.[2]	34 (86.4 cm)
ELECTRICAL DATA	
Horsepower[1]	1/5
Amps	2.6
Voltage	115/60/1
NEMA	5-15P
REFRIGERATION DATA	
Refrigerant	R-290
Charge Amount oz.	3.0 (85 g)
BTU	1800

When ordering please specify:
Voltage and Options



NEMA 5-15P

1. Based on 90°F ambient & 20°F evaporator.
2. Overall height includes 4” (10.2 cm) for casters.

Models listed to applicable UL, CSA, and NSF standards by an approved NRTL. Consult the factory or unit data plate for additional information.

Specifications subject to change without notice. Chart dimensions are rounded up to the nearest 1/16” (centimeters rounded up to the nearest tenth).

2026 © Traulsen • 4401 Blue Mound Road | Fort Worth, TX 76106 • 1 (800) 825-8220 • www.traulsen.com

C SERIES

2-SECTION COMPACT 4-DRAWER UNDERCOUNTER REFRIGERATOR

Project Name:	Location:		AIA #:
Item #:	Qty:	Model #:	SIS #:

REFRIGERATION SYSTEM

• Self-contained, rear-mounted system uses environmentally friendly, minimal GWP R-290 refrigerant

• Front-breathing system allows zero-clearance installation

• Easy access to condenser coil for cleaning

• High performance, balanced system operates at 32-41°F (0-5°C) to maintain consistent, food-safe temperatures

• LED display for microprocessor control is water-resistant

• Capillary tube metering device

CABINET CONSTRUCTION

• Stainless steel exterior and interior

• Exterior top, back, and bottom is constructed of heavy gauge galvanized steel

• Drawer exterior, liner and frame are constructed of stainless steel

• Cabinet is insulated with an average of 2-3/8" (6.03 cm) thick high density, non-CFC foamed-in-place polyurethane

• A set of (4) 4" (10.2 cm) high casters; (2) with brakes, (2) without brakes; factory-installed

• 9' cord & plug provided

DRAWERS

• Foamed-in-place, recessed handles

• Drawers are self-closing with a stay-open feature

• Magnetic, snap-in drawer gaskets

• Gasket-protecting retainers

• Removable without tools

• Accommodates (1) 6" deep full size pan per drawer; provided by others

FIELD-INSTALLED OPTIONS

• Single overshelf, 60"W x 18"H x 16"D (CLUCACC-60OSHELF)

• Set of (4) 6" (15.2 cm) legs


• Set of (4) 6" (15.2 cm) casters

• Set of (4) 2-3/4" (7 cm) casters


WARRANTY

Both a six-year parts and labor warranty, and an additional one-year compressor parts warranty (for a total of seven years) are provided standard

DOOR + DRAWER CONFIGURATIONS



CLUC-60R-DW-LD



CLUC-60R-DW-DR

CAD and/or Revit Files Available

https://traulsen.kclcad.com

Approved by:	**Approved by:**	**Date:**

2026 © Traulsen • 4401 Blue Mound Road | Fort Worth, TX 76106 • 1 (800) 825-8220 • www.traulsen.com