

SPH615

Product Family	Dishwasher
Subfamily	Hoodtype dishwasher
Basket dimensions	600x500 and 500x500 mm
Panel	Easyline 2016
Filter	5-stages filter system
Rinse pump with H.T.R. system	Rinse pump with atmospheric boiler
Dual Heating function	Yes
Usable load height	470 mm
Default power supply	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Maximum height with hood open	2138 mm
Dimensions	734x750x1523 mm
EAN code	8017709337261



Target

Potential users	Restaurants/Catering; Bakery/Pastry making; Industrial pastry&bakery laboratories; Butcher's shops; Meat processing industry; Schools
-----------------	--

Aesthetics

Series	Topline	Led colour	Green
Control Panel	Electronic		

Functions



Functions	Euronorm trays washing; GN 1/1 trays washing; 5- stage filter; HTR; Door clearance 470mm
-----------	---

Programmes

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs; Cold water rinse program
Program options	Extra rinse; Clean water cycle

Program specifications

Boiler 85°C/Tank 60°C-60"; Boiler 71°C/Tank 60°C-1'20";
Boiler 85°C/Tank 60°C-1'10"; Boiler 85°C/Tank 60°C-
1'30"; Boiler 71°C/Tank 60°C-2'10"; Boiler 85°C/Tank
60°C-2'40"; Boiler 85°C/Tank 60°C-4'10"

Drain and self cleaning cycle

Yes

Maximum baskets/hour

60

Maximum plates/hour

1320

Interface

Display 8 digit

On/off indicator Yes

Low rinse aid alert Yes

Low detergent alert Yes

Cycle progress indicator Yes

End of cycle indicator Yes

Manual diagnostics Yes

Construction

Tank Deep drawn

Construction Double wall

Tank material Stainless steel AISI 304

Back panel Stainless steel

Tank filter Stainless steel

Wash arm Stainless steel AISI 304

Rinse arm Stainless steel AISI 304

Hood Double skinned

Wash tank capacity 22 l

Boiler capacity 10 l

Protection class IPX4

Adjustable feet Yes

Net weight (kg) 129,000 kg

Drain max. height 1000 mm

Technical Features

Tank heating element 2200 W

Boiler heating element 9000 W

Wash pump 700 W

Default connection 9700 W

Water consumption per cycle 3,2 l

Warm water connection 8°C

Inlet water maximum temperature 60°C

Max water hardness 12°f - 7°dH

Water inlet pressure 100-1000 kPa

Electrical Connection

Electrical connection options 230 V 3~ / 26 A / 9,7 kW / 50 Hz; 230 V 3~ / 26 A / 9,7 kW (NC); 230 V~ / 16 A / 3,7 kW / 50 Hz; 230 V~ / 16 A / 3,7 kW / 50 Hz (NC); 230 V~ / 30 A / 6,7 kW / 50 Hz (NC); 230 V~ / 30 A / 6,7 kW / 50 Hz; 400 V 3N~ / 16 A / 9,7 kW / 50 Hz (NC)

Equipment


Drain pump Yes

Rinse aid flow rate 0.4 l/h

Peristaltic detergent pump	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse aid pump	Yes, electronic control	Break tank	Yes
Chemical level probe	Yes, optional KITSONLIV	Partial water exchange in the wash tank via built-in drain pump	Yes
Chemical dosing	gr/lt	600x400 mm tray/box washing option	Yes
Boiler thermostat	Yes	Trays washing option	GN1/1 530X32 5mm
Soft Start	Yes	Water supply pipe diameter	16 mm
Stand-by system	Yes	Drain supply pipe diameter	21.5 mm
Automatic start	Yes	Detergent (red) hose length	Yes, manual
Detergent flow rate	1.5 l/h	Rinse aid (blue) hose length	Yes, manual

Accessories Included

Plate basket	PB60D01	Water supply pipe	Yes - 2m
Cutlery basket	PHOOS03	Drain pipe	Yes - 2m
Flat basket	PB60G01		



Not included accessories



PHOOS01

Single basket in polypropylene for cutlery



PHOOS02

Basket in polypropylene for cutlery with 6 compartments




WH00S01

Wire insert for 12 small dishes



PB50G01

Universal basket in polypropylene 500x500



PB50D01

Basket made of polypropylene for 18 plates 500x500



PHOOS03

Basket in polypropylene with 6 compartments for cutlery for Capote



WB50G01

Universal wire basket with flat bottom 500x500



WB50D01

Wire basket for 18 dishes and trays 500x500



WB50G04

Wire basket for glasses with inclined bottom 500x500



WB50G02

Wire basket for glasses with inclined bottom 500x500



KITSONLIV

Probe level kit



PB60G01

Universal basket in polypropylene 600x500



PB60D01

Basket in polypropylene for 22 dishes 600x500



PB60T02

Basket for trays GN1/1 600x500



WB60G01

Wire basket with flat bottom 600x500



WB60D01

Wire basket for 24 dishes 600x500



WB60D02

Wire basket for 24 dishes 600x500




WB60T03

Wire basket for 5 trays 600x500

PB50G02

Universal basket in polypropylene
500x500



Symbols glossary



SUITABLE FOR EURONORM TRAY



Suitable for 1/1GN trays



HTR rinsing system



5 STAGE FILTER



MAX. USABLE HEIGHT 470mm