

PASS THRU STATION ICE CHEST



SS24IC10 shown
Covers sold separately

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS
SS24IC10
SS30IC10
SS24IC20*
SS30IC20*

**With Dual 10-Circuit Cold Plates*

SHORT DESCRIPTION

SS Series Ice Chests are intended to work with other underbar components to create a bartender/wait staff workstation.

FEATURES & BENEFITS

- All stainless for durable easy to clean surfaces
- Fully insulated to reduce ice melt in warm climates
- Highly efficient cold plates instantly chill your soft drinks to the correct temperature
- "2" Foamed-in-place insulation provides energy savings using Ecomate(tm), a blowing agent that has zero-ozone depletion and zero global warming potential
- Pass-thru design allowing both the bartender and cocktail server access
- Dent-resistant ABS top ledge for better resilience in a fast-paced working bar.
- Available with 10 or 20 circuit cold plate to service both sides of the bin



MODEL NUMBERS - SS241C10, SS301C10, SS241C20, SS301C20

PASS THRU STATION ICE CHEST

MODEL NOS.	SS241C10	SS301C10	SS241C20	SS301C20
	With 10-Circuit Cold Plate		With Dual 10-Circuit Cold Plates	
LENGTH, INCHES (mm)	24 (610)	30 (762)	24 (610)	30 (762)
ICE CAPACITY, LBS. (kg)	185 (83.9)	235 (106.6)	185 (83.9)	235 (106.6)
# OF COLD PLATE CIRCUITS	1	1	2	2
FRONT & SIDES	Stainless steel, top rim ABS			
BOTTOM	Galvanized steel			
COVERS	Stainless steel, three-piece, removable			
INTERIOR	Stainless steel with 1/4" radius corners, welded and sealer with non-exposed cold plate. Interiors can be divided with accessory freestanding ice dividers			
INSULATION	Foamed-in-place polyurethane			
LEGS	1-5/8" tubular, stainless steel with 1" adjustable thermoplastic foot			
PLUMBING	Drain connection - 1/2" NPS male			
COLD PLATE	Cast aluminum plate concealed under ice chest liner. Cold plate has 2 full-length circuits and 8 half-length circuits. Connections - 5/16" O.D. stainless steel tubing with swagged end to accept standard 1/4" I.D. beverage tubing			
OPERATING SPECIFICATIONS	Each full circuit will deliver four 6 oz. drinks per minute at 40° continuously, or 40 oz. every three minutes in a single draw (flow rate 2 oz./sec, 75° ambient, 75° product)			
OPTIONAL ACCESSORIES	Front and Back Covers, 3 Plastic Wells, 4 Piece Cover Set, 3 Plastic Bottle Wells, S.S. Bottle Holder, 4 Piece Cover Set, S.S. Bottle Holder			

Note: Covers not included. Soda Chase not applicable; soda lines must be routed behind adjacent equipment (IC10 and IC models only).

Form No. Z2985
Rev 05/20/26

PASS THRU STATION ICE CHEST

