



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CCP-4G GD LC C CI 230V 1N 50Hz

19097964

05/05/2023

EU Model shown – UK models have castors as standard

**DENOMINATION:**

Refrigerated counter with glass doors and locks - Concept 700 Gastronorm with 4 doors.

**DESCRIPTION :**

- Structure built with AISI-304 stainless steel
  - 50 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
  - Forced draught cooling system inside the room.
  - Copper piping and aluminium flaps evaporator.
  - Digital display for electronic and digital control of temperature and defrosting.
  - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
  - Easier loading and unloading thanks to its door self-closing and stay open features.
  - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
  - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
  - Built-in drainage to get rid of waste liquids inside the unit.
  - Interior LED lighting (only for models with glass doors).
  - Embedded bottom and curved panels inside for easy cleaning and maintenance.
  - Height adjustable stainless steel legs.
  - 10 cm high splashback.
  - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
  - Tested in climatic class IV.
- Refrigerated counters with glass doors.  
VISIBILITY: Double pane door and anodised aluminium frame with double vacuum chamber.

**POSSIBLE OPTIONS :**

- Stainless Backing
- Legs instead of castors
- Without splashback
- Door frame resistance
- Granite worktop
- Left group
- Without breastplate
- Without Countertop
- Panoramic aperture

**STANDARD:**

- Glass door
- Locks
- Castors
- UK plug


**POSSIBLE ACCESSORIES :**

- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS



**DIMENSIONS**

X Width	2242 mm	X Gross width	2353 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	165,0 kg	Gross Weight	174,0 kg
Net volume	1,334 m <sup>3</sup>	Gross volume	1,941 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,230 kW
Amperage (A)	1,04 A
Voltage	230V - 1N
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,436 kW
Annual elec. consumption	1808,40 kWh
Power consumption 24h	4,95 kWh
Gross internal volume	581 L
Climate class	4
Cooling gas load	108,000 g
Clasif. Energy efficiency	C
Energy Efficiency Index	26,93 %

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

**OTHERS**

Number of doors	4
Condensation system	Vent.



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
CCP-4G GD LC C CI 230V 1N 50Hz

19097964

05/05/2023

EU Model shown – UK models have castors as standard

