



EB4FX - FilterFlow Counter-top Automatic Water Boiler - W 250 mm - 4.5 kW

Efficient both in its use of space and in its use of energy, the high-powered FilterFlow Automatic Water Boiler is perfect for busy staff rooms and anywhere where employees have to wait for the kettle to boil.

- ✓ Higher power model delivering an increased output per hour compared to the EB3FX
- ✓ Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- ✓ Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- ✓ Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- ✓ Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- ✓ 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- ✓ Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

Specifications

Summary

| | |
|-----------------------------|-----------------------------------|
| Range Name | FilterFlow |
| Power Type | Electric |
| Unit Type | Counter-top |
| Available in UK Only | No |
| UK Warranty | 2 Years Parts and Labour Warranty |
| Export Warranty | Contact your local dealer |
| GTIN Code | 5056105105558 |

Power and Performance

| | |
|----------------------------------|------------|
| Hot and Cold Water Output | No |
| Rapid Draw Off Litres | 11.0 |
| Total Power kW | 4.5 |
| Temperature Range °C | 70 - 98 |
| IP Rating | IP23 |
| Rapid Draw Off Cups | 55 |
| Hourly Output Litres | 45 |
| Hourly Output Cups | 225 |
| Temperature Control | Electronic |

Key Specifications

| | |
|------------------------|------------|
| Capacity Litres | 15.0 |
| Outlet | Single-tap |
| Dispense Lock | No |
| WRAS Approved | Yes |

Weights and Dimensions

| | |
|----------------------------------|------|
| Unit Height (External) mm | 596 |
| Unit Width (External) mm | 250 |
| Unit Depth (External) mm | 525 |
| Net Weight Kg | 13.4 |

Supply Connections

| | |
|---------------------------------------|-------|
| Requires Installation | Yes |
| UK 3 Pin Plug | No |
| Requires Hardwiring | Yes |
| Electrical Supply Rating Watts | 4,500 |
| Single Phase Amps | 20.0 |
| Single Phase Voltage | 230 |
| Water Connection BSPT | 3/4" |
| Water Connection Pressure Bar | 6.0 |

Shipping

| | |
|-------------------------|------|
| Packed Weight Kg | 16 |
| Packed Height cm | 53 |
| Packed Width cm | 69.5 |
| Packed Depth cm | 36.6 |

Available Accessories



| | |
|-------------|------------------------------|
| BR55 | EB3FX AND EB4FX WALL BRACKET |
| DP10 | DESCALER POWDER |

Available Accessories

FC04

EBFX WATER FILTER - FROM 2015

Technical Picture



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm