

ACR-180DG-332-RRC-C1 U

3-Section Refrigerated Counter



PRODUCT SERIES: ADVANCE
ITEM NUMBER: 889020877
COUNTRY OF ORIGIN: TURKEY

Hoshizaki Advance ACR-180DG-332-RRC-C1 U is a 3-section 1/1 GN refrigerated counter with 2 drawer sections with each 3 x 1/3 drawers, 1 drawer section with 2 x 1/2 drawers and a flat worktop. It has a net usable volume of 160 ltr. The height excluding castors is 700mm, castors = H 150mm (C1).

- Fan assisted cooling
- Automatic defrost with re-evaporation of defrost water
- Heavy duty cabinet and compressor compartment construction
- Climate class 4 cooling system enduring up to +40°C ambient temperature
- Exterior and interior of stainless steel
- Compartmentalized cooling unit that is available as one unit
- A compact slide out refrigeration unit for maintenance and service
- Removable condenser filter for cleaning or replacement
- 2/2 drawer set is compatible with 200mm deep GN container
- 3/3 drawer set is compatible with 100mm deep GN container
- Anti-tilt shelves
- Removable magnetic door gaskets with triple insulation area
- Pan-shaped inside base with rounded corners to catch fluids
- IP 21 water protection
- Matching design identity as the Advance cabinets



1 / 1 GN

OPTIONAL EXTRAS

Set of legs 130-180mm (L1)
Set of legs 135-200mm (L2)
Set of 4 Castors for 900mm Counter-top (C2)
Castor Extension Kit (extends height of castors by 50mm)
Flat worktop with 100mm splashback

WARRANTY PERIOD

5 Years on Parts & Labour

EXTERIOR

Stainless Steel

INTERIOR

Stainless

Refrigerant type: R290 / Refrigerant: 0.079 kg / CO2 equivalent: 0.237 kg

CERTIFICATIONS



Energy efficiency class	Energy efficiency class standard	Energy Efficiency Index (EEI)
C	ISO 22041-2019	45 EEI



HOSHIZAKI

ACR-180DG-332-RRC-C1 U




TECHNICAL SPECIFICATIONS

Temperature range	Shelf size	Volume, gross	Net usable volume	Power supply	Climate class	Sound level	Ref. capacity - at -10°C
-2/+8°C	1/1 GN	457 l	160 l	230V, 50Hz	4 (max. ambient temp. of 30 °C with 55% RH)	53 dB	446 W

SHIPPING SPECIFICATIONS

Width (packed)	Depth (packed)	Height (packed)	Gross weight	Width	Depth	Height	Net weight
1,830 mm	760 mm	1,050 mm	173 kg	1,780 mm	700 mm	850 mm	161 kg







Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.





HOSHIZAKI

ACR-180DG-332-RRC-C1 U



HOSHIZAKI

Hoshizaki Belgium
Hoshizaki Danmark
Hoshizaki Deutschland
Hoshizaki France
Hoshizaki Iberia
Hoshizaki Italia
Hoshizaki Middle East

info@hoshizaki.nl
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands info@hoshizaki.nl
Hoshizaki Norge salg@hoshizaki.no
Hoshizaki Sverige orderSE@hoshizaki.dk
Hoshizaki UK uksales@hoshizaki.uk
Export countries sales.ex@hoshizaki-europe.com
Other countries sales.ex@hoshizaki-europe.com

www.hoshizaki.uk