



Induced Energy

CS3000KH Induction Cooking Unit

Model CS3000KH (Ceran) or CS3000KH-P (Hidden).- Induction keep hot
Suitable for drop-in with ceran top or through lava stone invisible unit.



Product Specifications

Maximum Power	1.0W
Electrical Supply	220V to 240V AC 50Hz and 60Hz 13 amp single phase supply
Cord & Plug	Cord length 1.8m Moulded 13-amp plug fitted (UK) Appropriate plug for each export market
Weight	9.5kg
Dimensions (mm)	Drop-in case: 395 x 395 x 140mm Front control panel: 350 x 90mm (Optional) Ceran footprint: 400 x 400mm
Depth of Field	Up to 30mm
Safety Features	Pan detection; boil-dry protection; overheat prevention; clean filter warning
User Interface	Display panel: Clean filter warning; No Pan Present warning; Glass/Lava hot warning; Shutdown
Controls	Ergonomically designed knob with precise settings of 1 to 25
Bespoke Options	Overall design/size, Lava options, natural or coloured glazed
Warranty	2 years parts and labour, excluding lava stone top
CE	Approved
Stone	Maximum thickness of stone is 12mm. Lava stone is recommended

Induced Energy Ltd. Operate a continuous programme of product development and improvement. Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants NN13 7EB
Tel: 01280 705900 Email: sales@inducedenergy.com

