Model:

## 24" Back Bar Cooler/Direct Draw Beer Dispenser:

SDD-24-60

Solid Swing Door Direct Draw Beer Dispenser



## SDD-24-60

CABINET CONSTRUCTION
Standard, cabinet exterior
construction includes attractive, wear
resistant vinyl on steel in black finish.
Stainless exterior options available.
Standard interior construction utilizes
stainless steel walls, floor and ceiling.
REFRIGERATION
Refrigeration system uses R134a
refrigerant, which is CFC and
HCFC-free for compliance with
environmental safety concerns.
ELECTRICAL
Units wired at factory and ready for
connection to a 115/60/1 phase,
15 amp dedicated outlet.
TEMPERATURE
Oversized, factory balanced,
refrigeration system holds 33°F to
<b>38</b> °F ( <b>0</b> .5℃ to 3.3℃)
SANITATION
NSF-7 approved for packaged and
bottled product.
MODEL FEATURES:
Standard LED light inside of the
cabinet
Easily accessible condenser coil for
cleaning, and easy service access

Two-faucets column is option

Rough-In Data

us (NSF.

Intertek

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

		Cabinet Dimensions (inches / mm)			Capacity				
Model	Doors	L	D	Н	1/2 Barrels	HP	Voltage	Amps	NEMA Config.
SDD-24-60	2	60 3/4 1544	24 3/8 620	35 5/8 905	2		115V/60Hz 220V/50Hz		5-15P
Hoight doos not	88mm) for	draft arm	Dlug t		rios by count	·r\/			

• Height does not include 15 1/4" (388mm) for draft arm.

• Plug type varies by country.

• Height does not includes 3" casters.

Add: 3390 Enterprise Avenue, Hayward, CA 94545-3228

Tel: (510) 293-0189 Fax: (510) 293-0199 E-mail: info@sabacorpusa.com Website: www.sabacorpusa.com



## SDD-24-60 Plan View

