

# THAWSAFE TECHNICAL DATASHEET

## WTS75 THAWSAFE



### WTS75

| Dimensions (mm) | External | Internal |
|-----------------|----------|----------|
| Width           | 727      | 567      |
| Depth           | 941      | 807      |
| Height          | 1960     | 1411     |
| Door Opening    |          | 567      |

### Capacity

|                        |    |
|------------------------|----|
| Max load capacity (kg) | 75 |
|------------------------|----|

## KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners
- Intuitive touchscreen controller with simple to operate icon based menu
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing door
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked door
- Product does not exceed 5°C throughout the thawing process
- Natural hydrocarbon refrigerant
- Fitted with 8 of 2/1 GN nylon coated wire shelves
- Anti-tilt trayslides
- Cooking thawed food is quicker and safer than cooking from frozen - eliminating the risk of cold spots once cooking has finished
- Designed with forced air heating and cooling circuits which cycle alternatively keeping the food within the correct temperature range of 0°C to +5°C
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

## OPTIONS

- Stainless steel back



# THAWSAFE TECHNICAL DATA

|                   |                     |
|-------------------|---------------------|
| ThawSafe          | WTS75               |
| Temperature (°C)  | 0/+5                |
| Power Supply      | 220V/240V 50Hz/1Ph  |
| Fuse (Amps)       | 13                  |
| Defrost           | Automatic off cycle |
| Noise Level (dBA) | 59                  |

|                              |   |
|------------------------------|---|
| Fittings                     |   |
| 2/1 GN Shelves (530 x 650mm) | 8 |

|                                        |      |
|----------------------------------------|------|
| Electrical Data - Standard Refrigerant |      |
| Refrigerant                            | R290 |
| Start Up (Amps)                        | 6.8  |
| Running (Amps)                         | 6.8  |
| Heat Rejection (kW / 24hrs)*           | 692  |

IMPORTANT NOTES:

|                                                                                                    |                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *Heat rejection is evaporating at -10°C in 32°C Ambient                                            | Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice. |
| The WTS75 requires connection to a main drain                                                      |                                                                                                                                                                                |
| All refrigeration equipment requires adequate ventilation for efficient and effective performance. |                                                                                                                                                                                |

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

